

PRIMARY CORNER DESCRIPTION Sec. Cor. for 27, 28, 33 and 34

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GL0 survey by John A. McQuinn, Deputy Surveyor, under Contract #466, dated April 5, 1883 (DCSO records Vol. 6 Page(s) 2419)

-
- Set Cedar post 4 ft. long, 4" sq., 24" in the ground for cor. to secs. 27, 28, 33 and 34, mkd. T23S S27 on NE.; R6W S34 on SE.; S33 on SW.; and S28 on NW. face, with 1 notch on S. and 3 notches on E. edges, from which
- A Fir 6" dia., bears N.23°E., 81 lks. dist. mkd. T23S R6W S27 BT.
 - A Fir 6" dia., bears S.43½°E., 72 lks. dist. mkd. T23S R6W S34 BT.
 - A Fir 6" dia., bears S.74°W., 140 lks. dist. mkd. T23S R6W S33 BT.
 - A Fir 36" dia., bears N.80°W., 125 lks. dist. mkd. T23S R6W S28 BT.

BLM resurvey by Otis Gould, Joseph Gawron, and Orville Eggen, Cadastral Surveyors, under Group #244, surveyed June 1943/October 1957 (DCSO records Vol. 30 Page(s) 12680)

Point for the sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 30" long, 2" dia., 26" in the ground, with brass cap mkd:

T23SR6W	
S28	S27
S33	S34
1957	

- from which
- A Fir 18" dia., bears N.69°E., 21 lks. dist. mkd. T23S R6W S27 BT.
 - A Fir 6" dia., bears S.72°E., 35 lks. dist. mkd. T23S R6W S34 BT.
 - A Fir 12" dia., bears S.24°W., 91 lks. dist. mkd. T23S R6W S33 BT.
 - A Fir 8" dia., bears N.44°W., 36 lks. dist. mkd. T23S R6W S28 BT.

BLM Corrective Dependent Resurvey by Wayne L. Rogers; Boyd W. Peterson; Philip G. Griffin; Dale T. Bedell; Cadastral Surveyors; and Robert H. Browning, Surveying Technician - under Group #'s 1266, 1637 and 1688, - surveyed June 9, 1986/Aug. 22, 1995 - (DCSO records Vol. 51 Page(s) 19483-84)

Point for the Sec. cor. at proportionate distance. There is no remaining evidence of the original corner.
(Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec. Cor. for 27, 28, 33 and 34

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T23S	R6W
<u>S28</u>	<u>S27</u>
S33	S34

1994

from which bearing trees mkd. by Gould, Gawron, and Eggen
A fir, 25 ins. diam., bears N. 62° E., 33 lks. dist., with healed blaze.

A fir, 8 ins. diam., bears S. 84° E., 42 lks. dist., with healed blaze.

A fir, 20 ins. diam., bears S. 20° W., 80 lks. dist., with healed blaze.

and a bearing tree mkd. in 1986 under this group

A fir, 22 ins. diam., bears N. 49° W., 29 lks. dist., mkd.

T23S R6W S28 BT. (In 1994 this is a healed blaze.)

Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.

From this point, the cor. of secs. 27, 28, 33, and 34, erroneously reestablished by Gould, Gawron, and Eggen in 1943-57, bears N. 49° 33' 00" E., 0.125 chs. dist.; monumented with an iron post, 2½ ins. diam., firmly set, projecting 10 ins. above the ground, with brass cap marked and witnessed as described in the official record, except the SE. bearing tree bears S. 69° E. (record, S. 72° E.), and the NW. bearing tree is dead and down, bears N. 47° W., 35 lks. dist. (record, N. 44° W., 36 lks.) Amended the marks on the brass cap to read AM 1994 1957, reset the monument inverted, and obliterated the marks on the dead and down NW. bearing tree.

Scott Toldness - Crew: Jason Raver, N Peterson, & J Rookey - Dec. 17, 2021 - C.S. File 65/109-52

Found - A 3.25" brass cap, on iron pipe, semi-submerged in sloughing rock, from which:

A 30" Fir bears N.62°E., 21.78 ft dist (rec. 33 lks.), with healed blazes and tag by "PG 4/94"

An 8" dead fir bears S.84°E., 42 lks. dist., with healed blazes and tag by "PG 5/94"

A dead and down 20" fir bears S.20°W., 80 lks. dist, fell west.

A 19" Fir bears N.49°W., 19.14 ft dist. (rec. 29 lks.), with healed blazes

New - A 15" Fir bears S.31°E., 31.0 ft dist., scribed "T23SR6WS34BT" with LS washer and tag by 90216.

Continued next page

TOWNSHIP 23 RANGE 06 POINT IDENTIFIER # 400200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 27, 28, 33 and 34

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A 12" Fir bears S23°W, 12.5 ft dist scribed
"T23SR6WS33BT" with LS washer and tag by 90216.
Cleared area of debris.
Painted BTs with a 6" band at 6' high.
Added ferrous nails at side center of BTs.
Compass Declination 14½°E