

PRIMARY CORNER DESCRIPTION Sec. Cor. for 15, 16, 21 and 22

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by John A. McQuinn, Deputy Surveyor, under Contract #466, dated April 5, 1883 (DCSO records Vol. 6 Page(s) 2422)

-----  
Set Yew post 4 ft. long, 4" sq., 24" in the ground for cor. to secs. 15, 16, 21 and 22, mkd. T23S S15 on NE.; R6W S22 on SE.; S21 on SW.; and S16 on NW. face, with 3 notches on S. and E. edges, from which  
A Hemlock 8" dia., bears N.41°E., 7 lks. dist. mkd. T23S R6W S15 BT.  
A Hemlock 12" dia., bears S.81°E., 6 lks. dist. mkd. T23S R6W S22 BT.  
A Maple 6" dia., bears S.22°W., 33 lks. dist. mkd. T23S R6W S21 BT.  
A Fir 12" dia. bears N.31°W., 40 lks. mkd. T23S R6W S16 BT

BLM resurvey by Otis Gould, Joseph Gawron, and Orville Eggen, Cadastral Surveyors, under Group #244, surveyed June 1943/October 1957 (DCSO records Vol. 30 Page(s) 12684)

-----  
Point for the sec. cor., determined at record distance from three of the original bearing trees:  
A Hemlock 10" dia., bears N.46°E., 7 lks. dist., mkd. with T23 R6 BT, on the bark. (Rec. bearing N.41°E.)  
A Hemlock 12" dia., bears S.81°E., 6 lks. dist. with portions of scribe marks.  
A Maple 6" dia., bears S.22°W., 33 lks. dist. with portions of scribe marks.  
A Fir 34" dia., bears N.56°E., 40 lks. dist. mkd. T23 R6 BT, on the bark. (Rec. brg and dist., N.31°E., 10 lks.)

Set an iron post 36" long, 2" dia., over a cross (X) on solid bedrock and in a mound of stone, 6 ft. base, to top, with brass cap mkd.  
T23SR6W  
S16|S15  
S21|S22  
1957

from which  
A Hemlock 10" dia., bears N.41°E., 25 lks. dist. mkd. T23S R6W S15 BT.  
A Hemlock 10" dia., bears S.32½°E., 75 lks. dist. mkd. T23S R6W S22 BT.  
A Hemlock 7" dia., bears S.6°W., 99 lks. dist. mkd. T23S R6W S21 BT.  
A Hemlock 10" dia., bears N.64½°W., 75 lks. dist. mkd. T23S R6W S16 BT.

PRIMARY CORNER DESCRIPTION Sec. Cor. for 15, 16, 21 and 22

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Fd. and used in BLM Corrective Dependent Resurvey by Wayne L. Rogers; Boyd W. Peterson; Philip G. Griffin; Dale T. Bedell; Cadastral Surveyors; and Robert H. Browning, Surveying Technician - under Group #'s 1266, 1637 and 1688, - surveyed June 9, 1986/Aug. 22, 1995 - (DCSO records Vol. 51 Pg 19489)

BLM corrective & dependent resurvey by Wayne L. Rogers, Cadastral Surveyor & Robert H. Browning, Surveying Technician, under Group #1803 surveyed May/Nov.. 1996 - (DCSO records Vol. 52 Page(s) 19954-5)

-----  
From the cor. of secs. 15, 16, 21, & 22, monumented with an iron post, 2" diam., loosely set, projecting 24" above ground, with brass cap (properly) mkd. from which a bearing tree mkd. by Haines, in 1956, recorded in the Douglas County Surveyors Office, RM 1-17

A fir, 51" diam., bears N.54 $\frac{3}{4}$ °W., 29 lks. with fragmentary scribe marks visible.

and bearing trees mkd. by Gould, Gawron, and Eggen

A hemlock, 18" diam., bears N.37 $\frac{1}{2}$ °E., 25 lks., with healed blaze.

A hemlock, 28" diam., bears S.32 $\frac{1}{2}$ °E., 72 lks., with healed blaze.

A hemlock, 18" diam., bears S.7 $\frac{1}{2}$ °W., 97 lks., with healed blaze.

A hemlock, 22" diam., bears N.64 $\frac{1}{2}$ °W., 80 lks., with healed blaze.

Reset iron post 32" in the ground.

From this point, the BLM Geodetic Control Station No. EC 41179, at latitude 43°33'31.936"N., longitude 123°23'27.852"W (NAD 1927), determined by the NAVSTAR Global Positioning System, bears S.68°12'24"E., 41.905 chs. (mean bearing and sea level distance); monumented with an aluminum cap, 3 $\frac{1}{4}$ " diam., firmly set flush with the ground, with top mkd. EC 41179 GPS 1993.

BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral Surveyor, under Group No. 2308, Surveyed April/July 2010 - (DCSO records Vol. 57 Page(s) 22848)

-----  
The cor. of secs. 15, 16, 21, and 22, monumented with an iron post, 2" dia., firmly set, projecting 6" above a collar of stone, with a brass cap (properly) mkd.

from which bearing trees mkd. by Gould, Gawron, and Eggen

A hemlock, 24" dia., bears N.37 $\frac{1}{2}$ °E., 16.5 ft., with a healed blaze.

A hemlock, 32" dia., bears S.32 $\frac{1}{2}$ °E., 47.5 ft., with a healed blaze.

continued next page

TOWNSHIP 23 RANGE 06 POINT IDENTIFIER # 400400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 15, 16, 21 and 22

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A hemlock, 21" dia., bears S.7½°W., 64.0 ft., with a healed blaze.  
A hemlock, 24" dia., bears N.64½°W., 52.8 ft., with a healed blaze.  
and a bearing tree mkd. by Haines, in 1956  
A fir, 52" dia., bears N.54¾°W., 20.7 ft., with fragmentary scribe marks visible on bark blaze and a brass washer tacked in blaze mkd. WILFORD HAINES SURVEY 239 DRAIN, ORE. (Record, 19.1 ft.)  
Corner is located 40 ft. W. of a ravine, drains N.60°E., and 145 ft. W. of a creek, 4 ft. wide, course N.35°W.