

TOWNSHIP 23 RANGE 06 POINT IDENTIFIER # 400540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 9 and 10

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by John A. McQuinn, Deputy Surveyor, under Contract #466, dated April 5, 1883 (DCSO records Vol. 6 Page(s) 2425)

-----  
Set Hemlock post 3 ft. long, 3" sq., 24" in the ground for ¼ sec. cor. mkd. ¼ S on W. face, from which  
A Fir 6" dia., bears N.20°E., 32 lks. dist. mkd. ¼ S BT.  
A Fir 6" dia., bears s.21°W., 18 lks. dist. mkd. ¼ S BT.

BLM resurvey by Otis Gould, Joseph Gawron, and Orville Eggen, Cadastral Surveyors, under Group #244, surveyed June 1943/October 1957 (DCSO records Vol. 30 Page(s) 12687)

-----  
Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 3 ft. long, 1" dia., 30" in the ground, with brass cap mkd:

¼  
S9|S10  
1955

from which

A Fir 10" dia., bears N.38½°E., 33 lks. mkd. ¼ S10 BT.  
A Fir 18" dia., bears N.71°W., 83 lks. mkd. ¼ S9 BT.

BLM resurvey by Joel R Herzberg, Cadastral Surveyor under Group No. 2778 - surveyed May 2015/July 2016 - (DCSO records Vol. 59 Page(s) 23552)

-----  
The ¼ sec. cor. of secs. 9 & 10, monumented with an iron post, 1" dia., firmly set, projecting 7" above the ground, with a brass cap (properly) mkd.

from which the BTs mkd. by Gould, et. al., in 1943-57

A fir, 33" dia., bears N.38½°E., 21.8 ft., with a healed blaze.

A fir stump with tin cap, 23" dia., bears N.71°W., 54.8 ft., with no marks visible.

and a new bearing tree

A fir, 18" dia., bears N.21¼°W., 6.6 ft., mkd. ¼ S9 BT.