

PRIMARY CORNER DESCRIPTION Sec. Cor. for 3, 4, 9 and 10

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by John A McQuinn, Deputy Surveyor, under Contract #466, dated April 5, 1883 (DCSO records Vol. 6 Page 2426)

Set Cedar post 4 ft. long, 4" sq., 24" in the ground for cor. to secs. 3, 4, 9 and 10, mkd. T23S S3 on NE; R6W S10 on SE; S9 on SW; & S4 on NW face, with 5 notches on S & 3 notches on E edges, from which

- A Dogwood 8" dia. bears N.15°E., 6 lks mkd. T23S R6W S3 BT
- A Maple 6" dia., bears S.26°E., 50 lks mkd T23S R6W S10 BT
- A Fir 8" dia., bears S.31°W., 30 lks mkd. T23S R6W S9 BT
- A Maple 10" dia., bears N.60°W., 50 lks mkd T23S R6W S4 BT

BLM resurvey by Otis Gould, Joseph Gawron, and Orville Eggen, Cadastral Surveyors, under Group #244, surveyed June 1943/October 1957 (DCSO records Vol. 30 Page(s) 12688)

Point for the sec. cor., at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 3 ft. long, 2" dia., 30" in the ground, with brass cap mkd:

T23SR6W
S 4 | S 3
S 9 | S10
1955

from which

- A Cedar 12" dia. bears N.51½°E., 34 lks mkd T23S R6W S3 BT
- A Cedar 12" dia. bears S.65½°E. 46 lks mkd T23S R6W S10 BT
- A Dogwood 16" dia bears S.16½°W. 37 lks mkd T23S R6W S9 BT
- A Fir 18" dia., bears N.7°W., 42 lks. mkd. T23S R6W S4 BT

BLM resurvey by Joel R Herzberg, Cadastral Surveyor under Group No. 2778 - surveyed May 2015/July 2016 - (DCSO records Vol. 59 Page(s) 23552-3)

The cor. of secs. 3, 4, 9, 10, monumented with an iron post, 2" dia., firmly set, projecting 6" above the ground with brass cap (properly) mkd.

from which the remains of the BTs mkd. by Gould, in 1943-57

- A cedar, 27" dia., bears N.51½°E., 22.4 ft., with a healed blaze.
- A cedar stump, 38" dia., bears S.65½°E., 30.4 ft., with no marks visible.
- A root hole, bears N.7°W., 27.7 ft., downhill of which is a fallen, decayed fir log, size indeterminate, with scribe marks T23S R6W S4 BT visible on decayed blaze.

and new bearing trees

- A fir, 15" dia., bears N.1½°E. 2.9 ft. mkd. T23S R6W S4 BT
- A fir, 21" dia., bears S.87¼°E., 49.5 ft., mkd. T23S R6W S10 BT.

continued next page

TOWNSHIP 23 RANGE 06 POINT IDENTIFIER # 400600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 3, 4, 9 and 10

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

A fir, 9" dia., bears S.25¼°W., 13.3 ft., mkd. T23S R6W S9
BT.

NAD 1983 (2011)

Latitude: 43° 35' 27.92" N. Longitude: 123° 24' 14.15" W.