TOWNSHIP 23 RANGE 06 POINT IDENTIFIER # 400640

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 3 and 4

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by John A. McQuinn, Deputy Surveyor, under Contract #466, dated April 5, 1883 (DCSO records Vol. 6 Page(s) 2428)

Set Yew post 3 ft. long, 3" sq., 24" in the ground for ¼ sec. cor. mkd. ¼ S on W. face, from which
A Maple 8" dia., bears N.21°E., 43 lks. dist. mkd. ¼ S BT
A Fir 7" dia., bears N.71°W., 29 lks. dist. mkd. ¼ S BT.

BLM resurvey by Otis Gould, Joseph Gawron, and Orville Eggen, Cadastral Surveyors, under Group #244, surveyed June 1943/October 1957 (DCSO records Vol. 30 Page(s) 12689)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 3 ft. long, 1" dia., 28" in the ground, with brass cap mkd:

¼
S 4|S 3
1955

from which
A Chinquapin 15" dia., bears S.74°E., 40 lks. dist. mkd. ¼ S3 BT.
A Fir 18" dia., bears N.77°W., 87 lks. dist. mkd. ¼ S4 BT.

BLM rehabilitation of certain corners, Timothy J. Moore, Cadastral Surveyor & Robert H. Browning, Surveying Tech., under Group #2000, Surveyed April 2002, - (DCSO records Vol. 54 Page(s) 21109-10)

The ¼ sec. cor. of secs. 3 & 4, monumented with an iron post, 1" dia., firmly set, projecting 5" above ground, with brass cap (properly) mkd.,
from which the remains of BTS mkd. by Gould, Gawron, & Eggen
A sawed chinquapin stump 20" dia. bears S.36½°E. 37.0 ft., with a healed blaze. (Record, S.74°E., 26.4 ft.)
and new bearing trees
A fir, 12" dia., bears S.63¼°E., 21.3 ft., mkd. ¼ S3 BT.
A fir, 13" dia., bears S.59¾°W., 12.0 ft., mkd. ¼ S4 BT.
The geographic position (NAD 1983) of this cor. as determined by a differentially corrected, mapping grade GPS receiver (Trimble Pro XR), observation, is as follows:
Latitude:43°35'54.85"N., Longitude: 123°24'18.46"W.