

TOWNSHIP 23 RANGE 06 POINT IDENTIFIER # 440600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 3 and 10

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by John A. McQuinn, Deputy Surveyor, under Contract #466, dated April 5, 1883 (DCSO records Vol. 6 Page(s) 2427)

Set Cedar post 3 ft. long, 3" sq., 24" in the ground for ¼ sec. cor. mkd. ¼ S on N. face, from which
A Fir 10" dia., bears N.14°E., 10 lks. dist. mkd. ¼ S BT.
A Maple 6" dia., bears S.26°W., 20 lks. dist. mkd. ¼ S BT.

BLM resurvey by Otis Gould, Joseph Gawron, and Orville Eggen, Cadastral Surveyors, under Group #244, surveyed June 1943/October 1957 (DCSO records Vol. 30 Page(s) 12688-89)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 3 ft. long, 1" dia., 26" in the ground, with brass cap mkd:

¼ $\frac{S \ 3}{S \ 10}$
1955

from which

A Maple 12" dia., bears N.68°W., 116 lks. dist. mkd. ¼ S3 BT.

A W.Fir 24" dia., bears S.6½°E., 141 lks. dist. mkd. ¼ S3 BT.