

PRIMARY CORNER DESCRIPTION No. 1/4 Cor. Section 3 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 4 Page(s) 1427)

Set Standard ¼ sec. post, from which
A Fir 10" dia., bears S.28°E., 40 lks. dist.
A Fir 12" dia., bears S.20°W., 31 lks. dist.

GLO survey by Carl S. Nicklin, Deputy Surveyor, under Special Instructions dated Oct. 27, 1897 (DCSO records Vol 4 Pg 1472)

The Standard ¼ sec. cor. on the N. Bdy. of Sec. 3, which I reestablish from the bearing tree, which bears S.28°E., 40 lks. dist., as follows:
Set a Cedar post, 3 ft. long, 5" sq., 24" in the ground, mkd. S C ¼ S on S., from which
A Fir 8" dia., bears S.28°E., 40 lks., mkd. S C ¼ S BT.
A Fir 24" dia., bears S.72°W., 66 lks., mkd. S C ¼ S BT.
This cor. is on the N. slope of spur, 50 ft. above creek.

BLM resurvey by Otis Gould, Joseph Gawron, and Orville Eggen, Cadastral Surveyors, under Group #244, surveyed June 1943/October 1957 (DCSO records Vol. 30 Page(s) 12627)

The standard ¼ sec. cor., the badly weathered and rotted remains of an old post, firmly set, with scribe marks visible and original bearing trees as follows:
A Fir 20" dia., bears S.28°E., 40 lks., marks grown over.
A Fir 36" dia., bears S.72°W., 66 lks., marks grown over.
At the corner point
Set an iron post, 3 ft. long, 1" dia., 27" in the ground, with brass cap mkd:

¼ S 3
S C
1943

Deposit the remains of the weathered stake alongside the iron post.

Fd. OK, June 1992, J. Branch, M 115-26 and M 115-23

Ken Hoffine - Crew: Gary Angiolet - For: Lone Rock Timberland Co. - Feb. 2017 - C.S. File 65/95-28

Found - 1943 GLO brass cap.
45" D.Fir bears S.73°W., (rec. from BLM field notes Vol. 30 Pg 12627 S.72°W., 43.56 ft)
New - 14" D.Fir bears S.21¼°E., 4.2 ft. we scribe T23S R6W ¼ S3 BT and tag tree.
Note - The north ¼ corner for sec. 3 lies approx. 35 ft. west of old skid road. There are a number of trees that have blown over near the corner. We put metal U-post approx. 0.5 ft. north of corner.