

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 26 and 27

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by John A. McQuinn, Deputy Surveyor, under Contract #466, dated April 5, 1883 (DCSO records Vol. 6 Page(s) 2410)

Set Dogwood post 3 ft. long, 3" sq., 24" in the ground for ¼ sec. cor., mkd. ¼ S on W. face, from which
A Fir 6" dia., bears S.22°W., 18 lks. dist. mkd. ¼ S BT.
A Fir 10" dia., bears N.23°E., 42 lks. dist. mkd. ¼ S BT.

BLM resurvey by Otis Gould, Joseph Gawron, and Orville Eggen, Cadastral Surveyors, under Group #244, surveyed June 1943/October 1957 (DCSO records Vol. 30 Page(s) 12670-71)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post 30" long, 2" dia., 28" in the ground with brass cap mkd:

T23SR6W
¼
S27 | S26
1957

from which

A Fir 14" dia., bears S.73°E., 93 lks. dist. mkd. ¼ S26 BT
A Fir 6" dia., bears S.86°W., 41 lks. dist. mkd. ¼ S27 BT.

Fd. and used in BLM resurvey by Jelley, Rogers and Bishop, under Contract #1098, surveyed June 1982/Nov. 1983 (DCSO records, Vol. 46 Page 17730)

BLM Corrective Dependent Resurvey by Wayne L. Rogers; Boyd W. Peterson; Philip G. Griffin; Dale T. Bedell; Cadastral Surveyors; and Robert H. Browning, Surveying Technician - under Group #'s 1266, 1637 and 1688, - surveyed June 9, 1986/August 22, 1995 - (DCSO records Vol. 51 Page(s) 19474)

Point for the ¼ sec. cor. at proportionate distance. There is no remaining evidence of the original corner.

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T23S R6W
¼
S27 | S26
1994

from which bearing trees mkd. by Gould, Gawron, and Eggen

A fir, 20 ins. diam., bears S. 70° E., 81 lks. dist., with healed blaze.

(Cont. Next Page)

TOWNSHIP 23 RANGE 06 POINT IDENTIFIER # 500240

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 26 and 27

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

A fir, 9 ins. diam., bears N. 86½° W., 52½ lks. dist., with healed blaze.
Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.
The corner is located on steep E. slope at NW. corner of logged area.

From this point, the ¼ sec. cor. of secs. 26 and 27, erroneously reestablished by Gould, Gawron, and Eggen in 1943-57, bears N. 63° 04' 00" W., 0.139 chs. dist.; monumented with an iron post, 2½ ins. diam., firmly set, projecting 2 ins. above the ground, with brass cap marked and witnessed as described in the official record. Amended the marks on the brass cap to read AM 1994 1957 and reset the monument inverted.

Scott Toldness - Crew: Jason Raver, N Peterson, & J Rookey - Jan. 12, 2022 - C.S. File 65/109-53

FOUND A 3.25" brass cap, on stainless steel pipe, flush with the ground, from which:
 A 25" Fir bears S.70°E., 53.5 ft. dist. (rec. 81 lks.), with healed blazes
 A 10" Fir bears N.86½°W., 35.0 ft dist. (no rec.), with healed blazes and tag by "PG 5/94"
New - Replaced BT tag on NW BT.
 Added BT tag on SE BT.
 Cleared area of debris.
 Painted BTs with a 6" band at 6' high.
 Added ferrous nails at side center of BTs.
 Compass Declination 14½°E