

PRIMARY CORNER DESCRIPTION Sec. Cor. for 22, 23, 26 and 27

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by John A. McQuinn, Deputy Surveyor, under Contract #466, dated April 5, 1883 (DCSO records Vol. 6 Page(s) 2410)

-----  
Set Cedar post 4 ft. long, 4" sq., 24" in the ground for cor. to secs. 22, 23, 26 and 27, mkd. T23S S23 on NE.; R6W S26 on SE.; S27 on SW.; and S22 on NW. face with 2 notches on S. and E. edges, from which  
A Fir 30" dia., bears N.10°E., 16 lks. dist. mkd. T23S R6W S23 BT.  
A Fir 7" dia., bears S.11°E., 21 lks. dist. mkd. T23S R6W S26 BT.  
A Fir 8" dia., bears S.43°W., 29 lks. dist. mkd. T23S R6W S27 BT.  
A Fir 6" dia., bears N.73°W., 52 lks. dist. mkd. T23S R6W S22 BT.

BLM resurvey by Otis Gould, Joseph Gawron, and Orville Eggen, Cadastral Surveyors, under Group #244, surveyed June 1943/October 1957 (DCSO records Vol. 30 Page(s) 12671)

-----  
Point for the sec. cor., at proportionate distance; there is no remaining evidence of the original corner.  
Set an iron post, 30" long, 2" dia., 24" in the ground, with brass cap mkd:  
T23SR6W  
S22 S23  
S27 S26  
1957

from which  
A Fir 6" dia., bears N.35°E., 18 lks. dist. mkd. T23S R6W S23 BT.  
A Fir 7" dia., bears S.85½°E., 38 lks. dist. mkd. T23S R6W S26 BT.  
A Fir 25" dia., bears S.29°W., 19 lks. dist. mkd. T23S R6W S27 BT.  
A Fir 9" dia., bears N.56°W., 10 lks. dist. mkd. T23S R6W S22 BT.

Cor. Fd. and used in BLM resurvey by Jolley, Rogers and Bishop under Contract #1098, surveyed June 1982/Nov. 1983, (DCSO records, Vol. 46 Page 17331)

BLM Corrective Dependent Resurvey by Wayne L. Rogers; Boyd W. Peterson; Philip G. Griffin; Dale T. Bedell; Cadastral Surveyors; and Robert H. Browning, Surveying Technician - under Group #'s 1266, 1637 and 1688, - surveyed June 9, 1986/August 22, 1995 - (DCSO records Vol. 51 Pages 19475-76)  
----- (Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec. Cor. for 22, 23, 26 and 27

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Point for the Sec. cor. at proportionate distance. There is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T23S R6W

S22 S23

S27 S26

1994

from which bearing trees mkd. by Gould, Gawron, and Eggen  
A fir, 8 ins. diam., bears N. 44½° E., 16½ lks. dist., with healed blaze. Add the marks X at breast height and BT at the base, facing corner position.

A fir, 32 ins. diam., bears S. 87° W., 34 lks. dist., with healed blaze.

A fir, 14 ins. diam., bears N. 59¼° W., 39 lks. dist., with healed blaze.

and a new bearing tree

A fir, 20 ins. diam., bears S. 68½° E., 22 lks. dist., mkd. T23S R6W S26 BT.

Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.

From this point, the cor. of secs. 22, 23, 26, and 27, erroneously reestablished by Gould, Gawron, and Eggen in 1943-57, bears N. 60° 32' 30" W., 0.293 chs. dist.; monumented with an iron post, 2 ins. diam., firmly set, projecting 15 ins. above the ground, with brass cap marked and witnessed as described in the official record, except the bearing to the NE. bearing tree is N. 26° E. (record, N. 35° E.), and the tree is now a snag. Amended the marks on the brass cap to read AM 1994 1957, reset the monument inverted, and obliterated the marks on the NE. bearing tree snag.