

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 22 and 23

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by John A. McQuinn, Deputy Surveyor, under Contract #466, dated April 5, 1883 (DCSO records Vol. 6 Page(s) 2412)

-----  
Set a Cedar post 3 ft. long, 3" sq., 24" in the ground for ¼ sec. cor., mkd. ¼ S on W. face, from which  
A Fir 30" dia., bears N.11°W., 18 lks. dist. mkd. ¼ S BT.  
A Fir 20" dia., bears S.53°E., 17 lks. dist. mkd. ¼ S BT.

BLM resurvey by Otis Gould, Joseph Gawron, and Orville Eggen, Cadastral Surveyors, under Group #244, surveyed June 1943/October 1957 (DCSO records Vol. 30 Page(s) 12673)

-----  
Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post 30" long, 2" dia., 26" in the ground, with brass cap mkd:

T23SR6W  
¼  
S22|S23  
1957

from which

A Fir 8" dia., bears S.78½°E., 26 lks. dist. mkd. ¼ S23 BT  
A Fir 9" dia., bears N.33½°W., 34 lks. dist. mkd. ¼ S22 BT

Douglas Co. Surveyors Office - A.Victor Cangie, James Cook, Karen Cheney, crew - May 18, 1976 - C.S. File 59/15-5

-----  
Found - I.P. 26" in ground, 2" dia., mkd. correctly, set in 1957, in good condition, with brass cap.

An 8" now 10" Fir bears S.76°E., (Rec. S.78½°E.) 17.2 ft. dist., in good condition with healed blaze.

A 9" Fir bears N.31½°W., (Rec. N.33½°W.) 22.5 ft., in good condition with healed blaze.

New BT - 21" D.Fir bears S.25½°W., 30.0 ft. mkd. "¼ S22 CS BT" in a double blaze.

Corner lies approx. 160 ft. East of NE flowing creek.

Fd. OK, April 1993, K.Hoffine, M 117-3

BLM Corrective Dependent Resurvey by Wayne L. Rogers; Boyd W. Peterson; Philip G. Griffin; Dale T. Bedell; Cadastral Surveyors; and Robert H. Browning, Surveying Technician - under Group #'s 1266, 1637 and 1688, - surveyed June 9, 1986/August 22, 1995 - (DCSO records Vol. 51 Page(s) 19478-79)

-----  
(Cont. Next Page)

TOWNSHIP 23 RANGE 06 POINT IDENTIFIER # 500340

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 22 and 23

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Point for the  $\frac{1}{4}$  sec. cor. at proportionate distance. There is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 22 ins. in the ground, with brass cap mkd.

T23S R6W

$\frac{1}{4}$

S22 | S23

1994

from which bearing trees mkd. by Gould, Gawron, and Eggen

A fir, 11 ins. diam., bears S.  $85\frac{1}{2}^{\circ}$  E., 21 lks. dist., with healed blaze.

A fir, 10 ins. diam., bears N.  $35^{\circ}$  W., 37 lks. dist., with healed blaze.

and a bearing tree mkd. by Langlitz, in 1975,

A fir, 24 ins. diam., bears S.  $32^{\circ}$  W., 44 lks. dist., with healed double blaze.

Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.

From this point, the  $\frac{1}{4}$  sec. cor. of secs. 22 and 23, erroneously reestablished by Gould, Gawron, and Eggen in 1943-57, bears N.  $51^{\circ} 57' 00''$  W., 0.058 chs. dist.; monumented with an iron post,  $2\frac{1}{2}$  ins. diam., firmly set, projecting 5 ins. above the ground, with brass cap marked and witnessed as described in the official record, except the NW. bearing tree is 32 lks. dist. (record, 34 lks.) Amended the marks on the brass cap to read AM 1994 1957 and reset the monument inverted.