

PRIMARY CORNER DESCRIPTION Sec. Cor. for 14, 15, 22 and 23

Alias	Description

GLO survey by John A. McQuinn, Deputy Surveyor, under Contract #466, dated April 5, 1883 (DCSO records Vol. 6 Page(s) 2412)

-
- Set Cedar post 4 ft. long, 4" sq., 24" in the ground for cor. to secs. 14, 15, 22 and 23, mkd. T23S S14 on NE.; R6W S23 on SE.; S22 on SW.; and S15 on NW face, with 3 notches on S. and 2 notches on E. edges, from which
- A Fir 6" dia., bears N.18°E., 21 lks. dist. mkd. T23S R6W S14 BT.
 - A Fir 10" dia., bears S.30°E., 169 lks. dist. mkd. T23S R6W S23 BT.
 - A Fir 6" dia., bears S.39°W., 17 lks. dist. mkd. T23S R6W S22 BT.
 - A Fir 6" dia., bears N.43°W., 72 lks. dist. mkd. T23S R6W S15 BT.

BLM resurvey by Otis Gould, Joseph Gawron, and Orville Eggen, Cadastral Surveyors, under Group #244, surveyed June 1943/October 1957 (DCSO records Vol. 30 Page(s) 12673-74)

Point for the sec. cor., at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post 30" long, 2" dia., 26" in the ground, with brass cap mkd:

T23SR6W
S15|S14
S22|S23
1957

- from which
- A Fir 6" dia., bears N.46°E., 38 lks. dist. mkd. T23S R6W S14 BT.
 - A Fir 10" dia., bears S.43°E., 62 lks. dist. mkd. T23S R6W S23 BT.
 - A Chinquapin 9" dia., bears S.56°W., 49 lks. dist. mkd. T23S R6W S22 BT.
 - A Fir 13" dia., bears N.10°W., 65 lks. dist. mkd. T23S R6W S15 BT.

BLM Corrective Dependent Resurvey by Wayne L. Rogers; Boyd W. Peterson; Philip G. Griffin; Dale T. Bedell; Cadastral Surveyors; and Robert H. Browning, Surveying Technician - under Group #'s 1266, 1637 and 1688, - surveyed June 9, 1986/August 22, 1995 - (DCSO records Vol. 51 Page(s) 19479-80)

Point for the sec. cor. at proportionate distance. There is no remaining evidence of the original corner.

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec. Cor. for 14, 15, 22 and 23

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a mound of stone, 2½ ft. base, to top, with brass cap mkd.

T23S R6W

S15 | S14

S22 | S23

1994

from which remains of bearing trees mkd. by Gould, Gawron, and Eggen

A sawed fir stump, 15 ins. diam., bears N. 57° E., 46 lks. dist., with healed blaze.

A fir, 30 ins. diam., bears S. 50° E., 70 lks. dist., with healed blaze.

and new bearing trees

A chinquapin, 10 ins. diam., bears S. 80½° W., 133 lks. dist., mkd. T23S R6W S22 BT.

A fir, 16 ins. diam., bears N. 51½° W., 237 lks. dist., mkd. T23S R6W S15 BT.

Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.

From this point, the cor. of secs. 14, 15, 22, and 23, erroneously reestablished by Gould, Gawron, and Eggen in 1943-57, bears N. 86° 23' 30" E., 0.111 chs. dist.; monumented with an iron post, 2 ins. diam., firmly set, projecting 14 ins. above the ground, and in a collar of stone, with brass cap marked and witnessed as described in the official record, except the NE. bearing tree is now a sawed stump, 37 lks. dist. (record, 38 lks.), the SW. bearing tree is uprooted, and the NW. bearing tree is now a sawed stump, bears N. 9° W., 55 lks. dist. (record, N. 10° W., 65 lks.) Amended the marks on the brass cap to read AM 1994 1957, reset the monument inverted, and obliterated the marks on the remains of the SW. and NW. bearing trees.

BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral Surveyor, under Group No. 2308, Surveyed April/July 2010 - (DCSO records Vol. 57 Page(s) 22843)

The cor. of secs. 14, 15, 22, and 23, monumented with an iron post, 2½" dia., firmly set, projecting 3" above a mound of stone, 3 ft. dia. 1 ft high, with a brass cap (properly) mkd. from which the remains of BTs mkd. by Gould, Gawron, & Eggen

A decayed fir stump, size indeterminate, bears N.57°E., 30.4 ft., with no marks visible.

A roothole bears S.50°E., 46.2 ft., alongside of which is a down fir snag, 30" dia., with no marks visible.

continued next page

TOWNSHIP 23 RANGE 06 POINT IDENTIFIER # 500400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 14, 15, 22 and 23

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

and bearing trees mkd. by Rogers, et al, in 1986-95
A chinquapin, 13" dia., bears S.80½°W., 87.8 ft., with fragmentary scribe marks visible on a partially healed blaze.
A fir, 22" dia., bears N.51½°W., 156.4 ft., with a healed blaze.
and new bearing trees
A fir, 8" dia., bears N.23¼°E., 4.5 ft., mkd. T23S R6W S14 BT.
A fir, 8" dia., bears S.61¾°E., 12.8 ft., mkd. T23S R6W S23 BT.
From this cor., a point erroneously reestablished by Gould, Gawron, and Eggen, bears N.86°17'48"E., 7.42 ft., monumented with an iron pipe, 2" dia., firmly set, top 3 ins. below ground surface.
Corner is located 65 ft. S. of a gravel road, 11 ft. wide, bears N.65°W. and S.80°E.