

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 14 and 15

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by John A. McQuinn, Deputy Surveyor, under Contract #466, dated April 5, 1883 (DCSO records Vol. 6 Page(s) 2413)

Set Cedar post 3 ft. long, 3" sq., 24" in the ground for ¼ sec. cor. mkd. ¼ S on W. face, from which
A Fir 18" dia., bears S.22°E., 19 lks. dist. mkd. ¼ S BT
A Fir 6" dia., bears S.33°W., 70 lks. dist. mkd. ¼ S BT.

BLM resurvey by Otis Gould, Joseph Gawron, and Orville Eggen, Cadastral Surveyors, under Group #244, surveyed June 1943/October 1957 (DCSO records Vol. 30 Page(s) 12675)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 30" long, 2" dia., 28" in the ground, with brass cap mkd:

T23SR6W
¼
S15|S14
1957

from which

A Fir 10" dia., bears N.61°E., 51 lks. dist. mkd. ¼ S14 BT

A Fir 15" dia., bears N.61°W., 55 lks. dist. mkd. ¼ S15 BT

This cor. falls in a ravine, 1 lks. wide, drains N.20°W.

Survey by Wilford N. Haines - For: Woolley Logging Co. - Nov. 1964 - M 30-51

Found - GLO brass cap in bed of stream.

SE BT down.

BT, N.61°W., 35.6 ft., dead.

Scribed -22" D.Fir S.74°W., 26.2 ft.

22" D.Fir S.06°E., 39.5 ft.

BLM Corrective Dependent Resurvey by Wayne L. Rogers; Boyd W. Peterson; Philip G. Griffin; Dale T. Bedell; Cadastral Surveyors; and Robert H. Browning, Surveying Technician - under Group #'s 1266, 1637 and 1688, - surveyed June 9, 1986/Aug. 22, 1995 - (DCSO records Vol. 51 Page(s) 19481-82)

Point for the ¼ sec. cor. proportionate distance. There is no remaining evidence of the original corner.

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T23S R6W
¼
S15 | S14
1994

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 14 and 15

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

from which bearing trees mkd. by Gould, Gawron, and Eggen
A fir, 29 ins. diam., bears S. 27 3/4° E., 65 lks. dist.,
with healed blaze.
A fir, 30 ins. diam., bears S. 60½° W., 24 lks. dist.,
with healed, double blaze.
Deposit a white "DEEP-1" magnetic marker at the base of the
stainless steel post.
The corner is located on a steep NE. slope, 15 lks. W. of
Snail Canyon Creek, 3 lks. wide, course irregularly N.

From this point, the ¼ sec. cor. of secs. 14 and 15,
erroneously reestablished by Gould, Gawron, and Eggen in
1943-57, bears East, 0.159 chs. dist.; monumented with an
iron post, 2½ ins. diam., firmly set, projecting 6 ins. above
the ground, with brass cap marked and witnessed as described
in the official record, except the SE. bearing tree bears S.
14° E., 59 lks. dist. (record, N. 61° E., 51 lks.), and the
SW. bearing tree bears S. 72° W., 39 lks. dist. (record, N.
61° W., 55 lks.). Amended the marks on the brass cap to read
AM 1994 1957 and reset the monument inverted.

BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral
Surveyor, under Group No. 2308, Surveyed April/July 2010 -
(DCSO records Vol. 57 Page(s) 22844)

The ¼ sec. cor. of secs. 14 and 15, monumented with an iron
post, 2½" dia., firmly set, projecting 2" above ground, with
a brass cap (properly) mkd.
from which the remains of a BT mkd. by Gould, Gawron, & Eggen
A sawed fir stump, 36" dia., bears S.27¾°E., 42.9 ft.,
with a healed blaze.
and a BT mkd. by Haines, PLS No. 239, in 1965, as an
accessory to the ¼ sec. cor. of secs. 14 and 15 erroneously
reestablished by Gould, Gawron, and Eggen, misidentified as
a bearing tree mkd. by Gould, Gawron, and Eggen, by Rogers,
et al, in 1986-95
A fir, 36" dia., bears S.60½°W., 15.8 ft., with a healed
double blaze and scribe marks 239 visible on bark.
and a new bearing tree
A hemlock, 16" dia., bears S.74¼°E., 42.6 ft mkd. ¼ S14 BT
Corner is located on a steep E. bank, 15 ft. W. of Snail
Creek, 4 ft. wide, course N.10°W.
NAD 1983 (CORS 96)
Latitude: 43°34'04.38"N. Longitude: 123°23'05.47"W.