

PRIMARY CORNER DESCRIPTION Sec. Cor. for 10, 11, 14 and 15

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by John A. McQuinn, Deputy Surveyor, under Contract #466, dated April 5, 1883 (DCSO records Vol. 6 Page(s) 2414)

-----  
Set Hemlock post 4 ft. long, 4" sq., 24" in the ground for cor. to secs. 10, 11, 14 and 15, mkd. T23S S11 on NE.; R6W S14 on SE.; S15 on SW.; and S10 on NW. face, with 4 notches on S. and 2 notches on E. edges, from which  
A Fir 36" dia., bears N.20°E., 100 lks. mkd. T23S R6W S11 BT.  
A Fir 24" dia., bears S.33°E., 28 lks. dist. mkd. T23S R6W S14 BT.  
A Fir 18" dia., bears S.70°W., 25 lks. dist. mkd. T23S R6W S15 BT.  
A Fir 48" dia., bears N.37°W., 19 lks. dist. mkd. T23S R6W S10 BT.

BLM resurvey by Otis Gould, Joseph Gawron, and Orville Eggen, Cadastral Surveyors, under Group #244, surveyed June 1943/October 1957 (DCSO records Vol. 30 Page(s) 12675-76)

-----  
The Sec. cor., determined at record bearings and distances from the remains of the original bearing trees:  
A Fir 46" dia., bears N.38°E., 100 lks. dist. scribe marks not legible, I re-mark alongside of old marks T23S R6W S11 BT.  
A Fir 36" dia., bears S.3°E., 28 lks. dist. mkd. T23S R6W S14 BT. I re-mark alongside of old marks T23S R6W S14 BT.  
A Fir 46" dia., bears N.67°W., 19 lks. dist. mkd. T23S R6W S10 BT. I re-mark alongside of old marks T23S R6W S10 BT.  
At the corner point  
Set an iron post, 3 ft. long, 2" dia., 27" in the ground, with brass cap mkd:  
T23SR6W  
S10|S11  
S15|S14  
1943  
from which  
A Fir 52" dia., bears S.41°W., 65 lks. dist. mkd. T23S R6W S15 BT.

Fd. OK, Feb. 1993, K.Hoffine, C.S. File 63/149-8

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec. Cor. for 10, 11, 14 and 15

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Fd. & Used in BLM Corrective Dependent Resurvey by Wayne L. Rogers; Boyd W. Peterson; Philip G. Griffin; Dale T. Bedell; Cadastral Surveyors; and Robert H. Browning, Surveying Technician - under Group #'s 1266, 1637 and 1688, - surveyed June 9, 1986/Aug. 22, 1995 - (DCSO records Vol. 51 Page(s) 19482)

BLM corrective and dependent resurvey by Wayne L. Rogers, Cadastral Surveyor & Robert H. Browning, Surveying Technician, under Group #1803 surveyed May/Nov. 1996 - (DCSO records Vol. 52 Page(s) 19967)

-----  
The cor. of secs. 10, 11, 14, & 15, monumented with an iron post, 1½ " diam., firmly set, projecting 6 " above ground, with brass cap mkd.

T 23 S R 6 W  
S 10 | S 11  
S 15 | S 14  
1943

- from which the remains of original bearing trees
- A fir, 51" diam., bears N.35 3/4° E., 97 lks., with a healed blaze.
  - A fir, 35" diam., bears S.5½°E., 25 lks., with scribe marks R 15 BT visible on the bark.
  - A sawed fir stump, 44" diam., bears N.64¼°W., 15 lks., with a healed blaze.
- and bearing trees mkd. by Gould, Gawron, and Eggen
- A fir, 65" diam., bears S.41°W., 61 lks., with healed blaze.
- and a new bearing tree
- A fir, 5" diam., bears N.23 3/4°W., 41½ lks., mkd. X BT.

BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral Surveyor, under Group No. 2308, Surveyed April/July 2010 - (DCSO records Vol. 57 Page(s) 22851)

-----  
The cor. of secs. 10, 11, 14, and 15, monumented with an iron post, 2" dia. (Record, 1½" dia.), firmly set, projecting 10" above ground, with a brass cap (properly) mkd.

- from which the remains of the original bearing trees
- A fir, 55" dia., bears N.35¾°E., 64.0 ft., with a healed blaze.
  - A fir, 40" dia., bears S.5½°E., 16.5 ft., with scribe marks 2 R 15 BT visible on bark.
  - A sawed fir stump, 47" dia., bears N.64¼°W., 9.9 ft., with a healed blaze.
- and a bearing tree mkd. by Gould, Gawron, and Eggen, reported by Rogers and Browning in 1996

continued next page

TOWNSHIP 23 RANGE 06 POINT IDENTIFIER # 500500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 10, 11, 14 and 15

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A fir, 74" dia., bears S.41°W., 40.3 ft., with a healed double blaze.  
and a bearing tree mkd. by Rogers and Browning in 1996  
A fir, 8" dia., bears N.23¾°W., 28.7 ft., with a healed double blaze. (Record, 27.4 ft.)