TOWNSHIP 23 RANGE 06 POINT IDENTIFIER # 500540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 10 and 11

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by John A. McQuinn, Deputy Surveyor, under Contract #466, dated April 5, 1883 (DCSO records Vol. 6 Page(s) 2415)

A Fir post 3 ft. long, 3" sq., 24" in the ground for ¼ sec. cor., mkd. ¼ S on W. face, from which
A Fir 36" dia., bears N.80°E., 34 lks. dist. mkd. ¼ S BT
A Fir 40" dia., bears S.24°W., 100 lks. dist. mkd. ¼ S BT

BLM resurvey by Otis Gould, Joseph Gawron, and Orville Eggen, Cadastral Surveyors, under Group #244, surveyed June 1943/October 1957 (DCSO records Vol. 30 Page(s) 12677)

The ¼ sec. cor. of secs. 10 and 11, determined at record bearing and distance to one of the original bearing trees:
A Fir 48" dia., bears N.80°E., 34 lks. dist., mkd. ¼ S BT
At the corner point
Set an iron post, 3 ft. long, 1" dia., 27" in the ground, with brass cap mkd:

¼
S10|S11
1943

from which
A Fir 24" dia., bears S.32°E., 112 lks. dist. mkd. ¼ S11 BT.
A Fir 30" dia., bears N.8°W., 75 lks. dist. mkd. ¼ S10 BT

Ken Hoffine - For: Lone Rock Timber Co. - Gary Angiolet & Iginaco Roman - 9/2/2009 - C.S. File 65/66-35

Found - 49" D.Fir stump bears N.8°W., 49.0 Ft. (Record N.8°W., 49.5 ft.) LRT Tag Healed Face
41" D.Fir snag bears S.33½°E., 75.2 Ft. (Record S.32°E., 73.92 ft.) Healed Face and Tag
1943 GLO BCIP
New - 5/8"x40" I.R. with yellow plastic cap marked LONE ROCK TIMBER PLS 2291 bears S.33°24'E., 25.9 Ft.
5/8"x40" I.R. with yellow plastic cap marked LONE ROCK TIMBER PLS 2291 bears S.5°10'E., 137.51 Ft.
5/8"x40" I.R. with yellow plastic cap marked LONE ROCK TIMBER PLS 2291 bears S.5°10'E., 177.84 Ft.
Note - Corner is 0.7 ft above ground, & approx. 50 ft east of draw and approx. 150 feet north of dirt road.