

PRIMARY CORNER DESCRIPTION Sec. Cor. for 2, 3, 10 and 11

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

GLO survey by John A. McQuinn, Deputy Surveyor, under Contract #466, dated April 5, 1883 (DCSO records Vol. 6 Page(s) 2415-16)

Set Cedar post 4 ft. long, 4" sq., 24" in the ground for cor. to secs. 2, 3, 10 and 11, mkd. T23S S2 on NE.; R6W S11 on SE.; S10 on SW.; and S3 on NW. face, with 5 notches on S. and 2 notches on E. edges, from which


- A Maple 8" dia., bears N.50°E., 58 lks. dist. mkd. T23S R6W S2 BT.
- A Maple 6" dia., bears S.16°E., 35 lks. dist. mkd. T23S R6W S11 BT.
- A Maple 10" dia., bears S.22°W., 33 lks. dist. mkd. T23S R6W S10 BT.
- A Hemlock 36" dia., bears N.30°W., 150 lks. mkd. T23S R6W S3 BT.

BLM resurvey by Otis Gould, Joseph Gawron, and Orville Eggen, Cadastral Surveyors, under Group #244, surveyed June 1943/October 1957 (DCSO records Vol. 30 Page(s) 12677-78)

The Sec. cor., the badly weathered remains of old stake, 30" long, 3" sq., firmly set, no legible scribe marks, from which

- A Fir 50" dia., bears S.80°E., 33 lks. dist. mkd. T23S R6W S11 BT under 60 years of overgrowth.

At the corner point
Set an iron post, 3 ft. long, 2" dia., 27" in the ground, with brass cap mkd:



from which

- A Cedar 25" dia., bears N.31 3/4°E., 88 lks. dist. mkd. T23S R6W S2 BT.
- A Fir 50" dia., bears S.79°E., 27 lks. dist. mkd. T23S R6W S11 BT.
- A Cedar 7" dia., bears S.10°W., 66 lks. dist. mkd. T23S R6W S10 BT.
- A Fir 36" dia., bears N.45°W., 117 lks. dist. mkd. T23S R6W S3 BT.

Douglas Co. Surveyors Office - Karen Reed, Terrie Plouff, crew May 25, 1982 - C.S. File 61/36-14

Found - 1943 GLO brass cap on 2" I.P., properly mkd. protruding 1.25 ft. above ground.
No original BTs found.
(Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec. Cor. for 2, 3, 10 and 11

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

25" Cedar now 34" bears N.31 3/4°E., 58.1 ft. with well healed double blaze.
 50" Fir now 56" bears S.79°E., 17.8 ft. with a well healed previously chopped open scar.
 Other BTs fall in slide area. Found no trace of BTs at record bearing and distances.
 Left 1943 Cap in position to perpetuate 1943 resurvey.
 New BTs -7" Ash bears S.43°W., 33.4 ft. Bark scribed "T23S R6W S10 CS BT" horizontally down tree trunk.
 7" Fir bears N.32°W., 14.7 ft. scribed "T23S R6W S3 CS BT" in a double blaze.
 Location is approx. 200 ft. ± southerly of Andrew Creek.

BLM corrective and dependent resurvey by Wayne L. Rogers, Cadastral Surveyor & Robert H. Browning, Surveying Technician, under Group #1803 surveyed May/Nov.. 1996 - (DCSO records Vol. 52 Page(s) 1998-9)

 The cor. of secs. 2, 3, 10, & 11, monumented with an iron post, 1" diam., firmly set, projecting 12 " above ground, with brass cap mkd.

T 23	S	R 6	W
S 3		S 2	
S 10		S 11	
1943			

from which the remaining original bearing tree
 A fir, 55" diam., bears S.80°E., 23½ lks., with healed blaze. (Record, 33 lks.)
 and the remains of a BT mkd. by Gould, Gawron, and Eggen
 A sawed cedar stump, 34" diam., bears N.31 3/4° E., 88 lks., with healed blaze.
 and bearing trees mkd. by Reed, Deputy County Surveyor, in 1982, recorded in the Douglas County Surveyors Office, CS file No. 61/36
 An alder, 8" diam., bears S.42½°W., 50 lks., with scribe marks R6W S10 CS BT visible on the bark.
 A fir, 9" diam., bears N.31°W., 22 lks., with healed double blaze.
 and a new bearing tree
 A fir, 8" dia., bears N.15½°E., 17 lks mkd T23S R6W S2 BT

BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral Surveyor, under Group No. 2308, Surveyed April/July 2010 - (DCSO records Vol. 57 Page(s) 22846)

 The cor. of secs. 2, 3, 10, & 11, perpetuated by the Douglas County Surveyor's Office in 1982, monumented with an iron post, 2" dia., firmly set, projecting 7" above a collar of stone, with a brass cap (properly) mkd. Cont.

PRIMARY CORNER DESCRIPTION Sec. Cor. for 2, 3, 10 and 11

Alias	Description
Alias	Description
Alias	Description
Alias	Description

from which a bearing tree mkd. by person(s) unknown, reported by Gould, Gawron, and Eggen, subsequently reported as an original bearing tree by Rogers and Browning in 1996

A fir, 60" dia., bears S.80°E., 15.5 ft., with a healed blaze.

and the remains of a BT mkd. by Gould, Gawron, and Eggen

A sawed cedar stump, 36" dia., bears N.29½°E., 58.1 ft., with a healed blaze. (Record, N.31¾°E.)

and the remains of bearing trees mkd. by the Douglas County Surveyor's Office, reported by Rogers and Browning in 1996

A sawed ash stump, 9" dia., bears S.44¾°W., 33.9 ft., with scribe marks W S10 CS BT visible on bark. (Record, alder, S.42½°W.)

A decayed fir stump, 8" dia., bears N.31°W., 14.5 ft., with no marks visible.

and a bearing tree mkd. by Rogers and Browning in 1996

A fir, 10" dia., bears N.10¾°E., 11.2 ft., with a healed blaze. (Record, N.15½° E.)

and new bearing trees

An alder, 9" dia., bears S.86½°W., 39.6 ft., mkd. T23S R6W S10 BT on bark.

A fir, 12" dia., bears N.21¾°W., 41.9 ft., mkd. T23S R6W S3 BT.

Corner is located 45 ft. N. of a draw, drains N.50°W.

NAD 1983 (CORS 96)

Latitude: 43°35'25.05"N. Longitude: 123°23'09.04"W.