

PRIMARY CORNER DESCRIPTION Standard cor. for Secs. 2 & 3 only

Alias	Description
Alias	Description
Alias	Description
Alias	Description

<p>GLO survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 4 Page(s) 1427)</p> <p>-----</p> <p>Set Standard cor. to secs. 2 and 3, from which A Fir 48" dia., bears S.24°E., 42 lks. dist. A Redwood 10" dia., bears S.27°W., 72 lks. dist.</p>
<p>GLO survey by Carl S. Nicklin, Deputy Surveyor, Special Instructions dated Oct. 27, 1897 (DCSO records Vol. 4 Page(s) 1471)</p> <p>-----</p> <p>The standard cor. of secs. 2 and 3, which I reestablish from the bearing trees, Set a Yew post, 3 ft. long, 4" sq., 24" in the ground, mkd. S C T23S R6W on S.; S2 on E.; and S3 on W.; faces, from which A Fir 50" dia., bears S.24°E., 42 lks. dist., mkd. T23S R65W S2 BT. A Cedar 10" dia., bears S.27°W., 72 lks. dist., mkd. T23S R6W S3 BT.</p>
<p>BLM resurvey by Otis Gould, Joseph Gawron, and Orville Eggen, Cadastral Surveyors, under Group #244, surveyed June 1943/October 1957 (DCSO records Vol. 30 Page(s) 12626)</p> <p>-----</p> <p>The standard cor. of secs. 2 and 3, determined at record bearing and distance from the original bearing trees: A Fir 54" dia., bears S.24°E., 42 lks. marks grown over. A Cedar 22" dia., bears S.27°W., 72 lks. dist., marks grown over.</p> <p>At the corner point Set an iron post, 3 ft. long, 2" dia., 27" in the ground, with brass cap mkd:</p> <p style="text-align: center;">----- S 3 S 2 T23SR6W S C 1943</p>
<p>Fd. B.C., June 1992, J.Branch, M 115-26 and M 115-23</p>
<p>BLM corrective and dependent resurvey by Wayne L. Rogers, Cadastral Surveyor &amp; Robert H. Browning, Surveying Technician, under Group #1803 surveyed May/Nov.. 1996 - (DCSO records Vol. 52 Page(s) 19959)</p> <p>-----</p> <p>The standard cor. of secs. 2 and 3 only, monumented with an iron post, 2" diam., firmly set, projecting 10" above ground, with brass cap mkd. continued next page</p>

TOWNSHIP 23 RANGE 06 POINT IDENTIFIER # 500700

PRIMARY CORNER DESCRIPTION Standard cor. for Secs. 2 & 3 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

S 3 S 2  
T 23 S R 6 W  
SC  
1943

from which the remains of an original bearing tree  
A roothole, bears S.24°E., 42 lks., with uprooted fir, 60"  
diam., alongside, no marks visible.  
and the remaining bearing tree mkd. by Nicklin  
A cedar, 27" diam., bears S.27°W., 72 lks., with healed  
blaze.  
and a new bearing tree  
A fir, 12" diam., bears S.74½°E., 17½ lks., mkd. T23S R6W  
S2 SC BT.