TOWNSHIP 23 RANGE 06 POINT IDENTIFIER # 540200

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 26 and 35

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by John A. McQuinn Deputy Surveyor, under Contract #466, dated April 5, 1883 (DCSO records Vol 6 Pg 2409)

Set Cedar post 3 ft. long, 3" sq., 24" in the ground for ¼ sec. cor. marked ¼ on N. face, from which
A Fir 10" dia., bears S.60°E., 15 lks. dist. mkd. ¼ S BT.
A Fir 8" dia., bears N.81°W., 30 lks. dist. mkd. ¼ S BT.

BLM resurvey by Otis Gould, Joseph Gawron, and Orville Eggen, Cadastral Surveyors, under Group #244, surveyed June 1943/October 1957 (DCSO records Vol. 30 Page(s) 12670)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post 30" long, 2" dia., 26" in the ground with brass cap mkd:

T23SR6W
¼ S 26
S 35
1957

from which
A Hemlock 8" dia., bears N.39°E., 120 lks., mkd. ¼ S26 BT.
A Fir 6" dia., bears S.11°E., 58 lks., mkd. ¼ S35 BT.

Cor. Fd. and used in BLM subd. of Sec. 26 by Jelley, Rogers and Bishop, Contract #1098, surveyed June 1982/Nov. 1983 (DCSO records, Vol. 46 Pages 17740-41) Note: Fd. Hemlock to be 122 lks. dist.

Cor. Fd. & Used in BLM Corrective Dependent Resurvey by Wayne L. Rogers; Boyd W. Peterson; Philip G. Griffin; Dale T. Bedell; Cadastral Surveyors; & Robert H. Browning, Surveying Technician - under Group #'s 1266, 1637 and 1688, - surveyed June 9, 1986/Aug. 22, 1995 - (DCSO records Vol. 51 Pg 19512)

BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral Surveyor, under Group No. 2308, Surveyed April/July 2010 - (DCSO records Vol. 57 Page(s) 22842)

The ¼ sec. cor. of secs. 26 and 35, monumented with an iron post, 2½" dia., firmly set, projecting 8" above ground, with a brass cap (properly) mkd.
from which bearing trees mkd. by Gould, Gawron, and Eggen
A hemlock, 26" dia., bears N.39°E., 80.5 ft., with no marks visible on a decayed, partially healed blaze.
A fir, 13" dia., bears S.11°E., 37.1 ft., with a healed blaze. (Record, 38.3 ft.)
Corner is located 80 ft. E. of a spur, slopes N.15°W.