

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 23 and 26

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO survey by John A. McQuinn, Deputy Surveyor, under Contract #466, dated April 5, 1883 (DCSO records Vol. 6 Page(s) 2411)

-----  
Set Cedar post 3 ft. long, 3" sq., 24" in the ground for ¼ sec. cor. mkd. ¼ S on N. face, from which  
A Willow 6" dia., bears S.30°W., 4 lks. dist. mkd. ¼ S BT.  
A Fir 12" dia., bears N.70°W., 6 lks. dist. mkd. ¼ S BT.

BLM resurvey by Otis Gould, Joseph Gawron, and Orville Eggen, Cadastral Surveyors, under Group #244, surveyed June 1943/October 1957 (DCSO records Vol. 30 Page(s) 12672)

-----  
Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 30" long, 2" dia., 28" in the ground, with brass cap mkd:

T23SR6W  
¼ S 23  
S 26  
1957

from which

A Madrone 8" dia., bears N.65°E., 39 lks. dist. mkd. ¼ S23 BT.

A Madrone 6" dia., bears S.61°W., 54 lks. dist. mkd. ¼ S26 BT.

Cor. Fd. and used in BLM resurvey by Jolley, Rogers and Bishop under Contract #1098, surveyed June 1982/Nov. 1983 (DCSO records, Vol. 46 Page 17732)

Fd. OK, April 1993, K. Hoffine, M 117-3

BLM Corrective Dependent Resurvey by Wayne L. Rogers; Boyd W. Peterson; Philip G. Griffin; Dale T. Bedell; Cadastral Surveyors; and Robert H. Browning, Surveying Technician - under Group #'s 1266, 1637 and 1688, - surveyed June 9, 1986/August 22, 1995 - (DCSO records Vol. 51 Page(s) 19476-77)

-----  
Point for the ¼ sec. cor. at proportionate distance. There is no remaining evidence of the original corner.

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T23S R6W  
S23  
¼  
S26  
1994

(Cont. Next Page)

TOWNSHIP 23 RANGE 06 POINT IDENTIFIER # 540300

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 23 and 26

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

from which  
A fir, 9 ins. diam., bears S. 41 3/4° E., 16½ lks. dist.,  
mkd. ¼ S26 BT.  
A fir, 8 ins. diam., bears N. 71 3/4° W., 16 lks. dist.,  
mkd. X at breast height and BT at base.  
Deposit a white "DEEP-1" magnetic marker at the base of the  
stainless steel post.

From this point, the ¼ sec. cor. of secs. 23 and 26,  
erroneously reestablished by Gould, Gawron, and Eggen in  
1943-57, bears N. 67° 04' 00" W., 0.198 chs. dist.;  
monumented with an iron post, 1 in. diam., firmly set,  
projecting 12 ins. above the ground, with brass cap marked  
and witnessed as described in the official record. Amended  
the marks on the brass cap to read AM 1994 1957, reset the  
monument inverted, and obliterated the marks on the bearing  
trees.