

PRIMARY CORNER DESCRIPTION S. Center 1/16 cor. Section 14

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

Survey by Wilford N. Haines - For: Woolley Logging Co. - Nov. 1964 - M 30-51

-----  
Set 1" x 1" x 36" T-Iron.  
Scribed -40" D.Fir N.66°W., 29.0 ft.  
26" D.Fir S.21°E., 7.8 ft.

BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral Surveyor, under Group No. 2308, Surveyed April/July 2010 - (DCSO records Vol. 57 Page(s) 22856)

-----  
The center S 1/16 sec. cor. of sec. 14, established by Haines, in 1964, and is accepted as the cor., monumented with a "T" shaped iron rod, 3/4" dia., firmly set, projecting 11" above ground, from which the remains of bearing trees mkd. by Haines

A forked fir, with 25 and 38" dia. trunks, bears S.26¼°E., 8.0 ft., with scribe marks 1/16 visible on bark.

A sawed fir stump, 42" dia., bears N.67¼°W., 28.8 ft., with a healed double blaze.

At the corner point

Set a stainless steel post, 28" long, 2½" dia., 24" in the ground, with a brass cap mkd.

C  
S 1/16 | S 14  
C  
2010

from which a new bearing tree

A fir, 6" dia., bears S.85½°W., 19.0 ft., mkd. CS 1/16 S14 BT.

Place the "T" shaped iron rod, 48" long, inside and deposit a magnet at the base of the stainless steel post.

Corner is located 20 ft. S. of a wide spur, slopes S.60°E., and 55 ft. N. of an unimproved dirt road, 8 ft. wide, bears N.35°W. and S.35°E.