

TOWNSHIP 23 RANGE 06 POINT IDENTIFIER # 540440

PRIMARY CORNER DESCRIPTION Center 1/4 Corner Sec. 14

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Survey by Wilford N. Haines - For: Woolley Logging Co. - Nov. 1964 - M 30-51

Set 1" x 1" x 36" T-Iron
Scribed -15" D.Fir N.86°W., 42.7 ft.
22" D.Fir S.58°E., 84.0 ft.

BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral Surveyor, under Group No. 2308, Surveyed April/July 2010 - (DCSO records Vol. 57 Page(s) 22856)

The center ¼ sec. cor. of sec. 14, established by Haines, in 1964, and is accepted as the cor., monumented with a "T" shaped iron rod, 3/4" dia., firmly set, projecting 8" above ground, from which bearing trees mkd. by Haines

A fir, 46" dia., bears S.59¼°E., 82.1 ft., with a healed blaze.

A fir, 36" dia., bears N.87¼°W., 42.4 ft., with a healed blaze.

At the corner point

Set a stainless steel post, 28" long, 2½" dia., 25" in the ground, with a brass cap mkd.

T 23 S R 6 W

C ¼ S 14

2010

Place the "T" shaped iron rod, 48 ins. long, inside and deposit a magnet at the base of the stainless steel post.