

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 11 and 14

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by John A. McQuinn Deputy Surveyor, under Contract #466, dated April 5, 1883 (DCSO records Vol 6 Pg) 2415)

-----  
Set a Fir post 3" sq., 3 ft. long, 24" in the ground for ¼ sec. cor., mkd. ¼ S on N. face, from which  
A Fir 6" dia., bears N.22°W., 18 lks. dist. mkd. ¼ S BT.  
A Fir 20" dia., bears S.16°E., 39 lks. dist. mkd. ¼ S BT

BLM resurvey by Otis Gould, Joseph Gawron, and Orville Eggen, Cadastral Surveyors, under Group #244, surveyed June 1943/October 1957 (DCSO records Vol. 30 Page(s) 12676)

-----  
Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.  
Set an iron post, 3 ft. long, 1" dia., 28" in the ground, with brass cap mkd:  
T23SR6W  
¼ S 11  
S 14  
1957

from which  
A Fir 6" dia., bears N.22°W., 6 lks. dist. mkd. ¼ S11 BT.  
A Fir 8" dia., bears S.9¼°E., 24 lks. dist. mkd. ¼ S14 BT

BLM corrective and dependent resurvey by Wayne L. Rogers, Cadastral Surveyor & Robert H. Browning, Surveying Technician, under Group #1803 surveyed May/Nov.. 1996 - (DCSO records Vol. 52 Page(s) 19966)

-----  
The ¼sec. cor. of secs. 11 & 14, monumented with an iron post, 1½" diam., firmly set flush with the ground, with brass cap (properly) mkd.  
from which a bearing tree mkd. by Gould, Gawron, and Eggen  
A fir, 14" diam., bears N.16¼°E., 6 lks., with a healed blaze. (Record, N.22°W.)  
and a new bearing tree  
A fir, 20" diam., bears S.6½°W., 110½ lks., mkd. ¼ S14 BT.  
From this point, the BLM, Geodetic Control Station No. EC 41179 bears S. 36° 23'03"W., 112.157 chs. dist. (mean bearing and sea level distance), hereinbefore described.

BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral Surveyor, under Group No. 2308, Surveyed April/July 2010 - (DCSO records Vol. 57 Page(s) 22857)

-----  
The ¼ sec. cor. of secs. 11 & 14, monumented with an iron post, 1½" dia., firmly set, flush with ground, with a brass cap (properly) mkd.

continued next page

TOWNSHIP 23 RANGE 06 POINT IDENTIFIER # 540500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 11 and 14

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

from which a bearing tree mkd. by Gould, Gawron, and Eggen  
A fir, 21" dia., bears N.22°W., 4.0 ft., with a healed  
blaze. (Record, N.16¼°E.)  
and a bearing tree mkd. by Rogers and Browning in 1996  
A fir, 27" dia., bears S.6½°W., 72.9 ft., with a healed  
blaze.  
Corner is located 30 ft. W. of a gravel road, 10 ft. wide,  
bears N.30°W. and S.30°E.