TOWNSHIP 23 RANGE 06 POINT IDENTIFIER # 600140

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 36 and 36

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #310, dated Nov. 30, 1878 (DCSO records Vol. 6 Page(s) 2394)

Set ¼ sec. post alongside of a boulder, 48" x 42", from which
A Fir 30" dia., bears S.3¼°E., 63 lks.
A Laurel 4" dia., bears S.89½°W., 33 lks.

BLM resurvey by Otis Gould, Joseph Gawron, and Orville Eggen, Cadastral Surveyors, under Group #244, surveyed June 1943/October 1957 (DCSO records Vol. 30 Page(s) 12658)

Point for the ¼ sec. cor. of secs. 35 and 36, at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 3 ft. long, 2" dia., 27" in the ground, with brass cap mkd:

¼
S35|S36
1943

from which
A Fir 30" dia., bears N.27°E., 50 lks., mkd. ¼ S36 BT.
A Fir 28" dia., bears S.69°W., 31 lks., mkd. ¼ S35 BT.

BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral Surveyor, under Group No. 2308, Surveyed April/July 2010 - (DCSO records Vol. 57 Page(s) 22834)

The ¼ sec. cor. of secs. 35 and 36, monumented with an iron post, 1" dia., firmly set, projecting 8" above ground, with a brass cap (properly) mkd.
from which the remains of BTs mkd. by Gould, Gawron, & Eggen
A decayed fir stump, size indeterminate, bears N.27°E., 33.0 ft., with no marks visible.
A roothole bears S.69°W., 20.5 ft.
and new bearing trees
A fir, 9" dia.., bears N.64¼°E., 36.5 ft., mkd. ¼ S36 BT.
A fir, 5" dia.., bears N.49°W., 8.4 ft., mkd. ¼ S35 BT.