

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 25 and 26

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #310, dated Nov. 30, 1878 (DCSO records Vol. 6 Page(s) 2396)

Set ¼ sec. post in timber flat, from which
A Fir 30" dia., bears N.70¼°W., 27 lks.
A Fir 30" dia., bears S.67°E., 25 lks.

March 14, 1879

GLO survey by John A. McQuinn, Deputy Surveyor, under Contract #466, dated April 5, 1883 (DCSO records Vol. 6 Page(s) 2398)

Set Cedar post 3 ft. long 3" sq., 24" in the ground for ¼ sec. cor. mkd. ¼ S on W. face, from which
A Fir 8" dia., bears N.71°W., 94 lks. dist. mkd. ¼ S BT
A Fir 14" dia., bears East, 77 lks. dist. mkd. ¼ S BT.

BLM resurvey by Otis Gould, Joseph Gawron, and Orville Eggen, Cadastral Surveyors, under Group #244, surveyed June 1943/October 1957 (DCSO records Vol. 30 Page(s) 12660)

The ¼ sec. cor., determined by reference to the record bearing and distance to one of the original bearing trees:

A Fir 30" dia., bears East, 77 lks. dist. mkd. ¼.

At the corner point

Set an iron post, 3 ft. long, 1" dia., 27" in the ground, with brass cap mkd:

¼
S26|S25
1943

from which

A Fir 14" dia., bears N.76 3/4°W., 60 lks. dist. mkd. ¼ S26 BT.

Douglas Co. Surveyors Office - Milo Godfrey, Deputy - V. Tracy and M. Stone, crew - Nov. 1962 - C.S. File 52/102-24

Found - I.P. with brass cap but cap burned and melted so badly it is impossible to read it.

Old Fir, East 50.8 ft., tree uprooted, dead and badly burned. No markings left.

No trace of NW BT, location falls in landing at end of logging road.

Alongside corner post, set alum. post 3½ ft. high.

New BTs -7" D.Fir N.11°E., 50.0 ft. mkd. ¼ S25 CS BT.

13" D.Fir N.42½°W., 86.0 ft. mkd. ¼ S26 CS BT.

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 25 and 26

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

BLM Resurvey - James E Jelley, Wayne L. Rogers, and Lance J. Bishop, Cadastral Surveyors Under Group # 1098 - Surveyed June 1982/Nov. 1983 (DCSO records Vol. 46 Page(s) 17728)

The ¼ sec. cor., monumented with an iron post, 1" dia., firmly set, projecting 4" above ground, with brass cap melted, no marks, from which the remains of an original bearing tree:

A root hole, bears East, 77 lks. dist., with a down Fir alongside, size indeterminate, no marks visible.
and the remains of bearing trees mkd. by Tracy in 1962:

A Fir 17" dia., bears N.11°E., 76 lks. dist., with healed double blaze.

A Fir snag 14" dia., bears S.41°W., 131 lks. dist., with scribe marks ¼ S26 CS BT visible on open double blaze.

At the corner point

Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap mkd:

T 23 S R 6 W
1/4
S 26 | S 25
1982

from which a new bearing tree

A Fir 4" dia., bears S.53½°W., 13½ lks. dist., mkd. X BT.
Deposit 1" dia. iron post alongside iron post.

Cor. Fd. and used in BLM Corrective Dependent Resurvey by Wayne L. Rogers; Boyd W. Peterson; Philip G. Griffin; Dale T. Bedell; Cadastral Surveyors; and Robert H. Browning, Surveying Technician - under Group #'s 1266, 1637 and 1688, -surveyed June 9, 1986/Aug. 22, 1995 - (DCSO records Vol. 51 Page(s) 19513)

BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral Surveyor, under Group No. 2308, Surveyed April/July 2010 - (DCSO records Vol. 57 Page(s) 22835)

The ¼ sec. cor. of secs. 25 and 26, perpetuated by Godfrey, in 1962, monumented with an iron post, 2½" dia., firmly set, projecting 6" above ground, with a brass cap (properly) mkd. from which the remains of a BT mkd. by McQuinn in 1883

A roothole bears East 50.8 ft alongside of which is a down fir snag, size indeterminate, with no marks visible
and the remains of BTs mkd. by Godfrey

A fir, 26" dia., bears N.11°E., 50.2 ft., with a healed blaze.

A decayed fir stump, size indeterminate, bears S.41°W., 86.5 ft., with no marks visible.

continued next page

TOWNSHIP 23 RANGE 06 POINT IDENTIFIER # 600240

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 25 and 26

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

and a BT mkd. by Jelley, Rogers, and Bishop in 1982-83
A fir, 10" dia., bears S.53½°W., 8.9 ft., with a healed
double blaze.