

PRIMARY CORNER DESCRIPTION Sec. Cor. for 23, 24, 25 and 26

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by John A. McQuinn, Deputy Surveyor, under Contract #466, dated April 5, 1883 (DCSO records Vol. 6 Page(s) 2398)

Set Cedar post, 4 ft. long, 4" sq., 24" in ground for cor. to secs. 23, 24, 25 and 26, mkd. T23S S24 on NE.; R6W S25 on SE.; S26 on SW.; and S23 on NW. faces, with 2 notches on S. and 1 notch on E. edges, from which
A Fir 6" dia., bears N.20°E., 87 lks. dist., mkd. T23S R6W S24 BT.
A Fir 6" dia., bears S.90°E., 80 lks. dist., mkd. T23S R6W S25 BT.
A Fir 6" dia., bears S.2°W., 96 lks. dist. mkd. T23S R6W S26 BT.
A Fir 6" dia., bears N.70°W., 46 lks. dist. mkd. T23S R6W S23 BT.

BLM resurvey by Otis Gould, Joseph Gawron, and Orville Eggen, Cadastral Surveyors, under Group #244, surveyed June 1943/October 1957 (DCSO records Vol. 30 Page(s) 12661)

The sec. cor., determined at record bearing and distance from the only remaining bearing tree:
A Fir 36" dia., bears S.90°E., 80 lks. dist., mkd. R6 S2 BT.
At the corner point
Set an iron post, 3 ft. long, 2" dia., 28" in the ground, with brass cap mkd:
T23SR6W
S23|S24
S26|S25
1957
from which
A Fir 9" dia., bears N.12°E., 33 lks. dist., mkd. T23S R6W S24 BT.
A Fir 30" dia., bears S.66°E., 5 lks. dist., mkd. T23S R6W S25 BT.
A Chinquapin 10" dia., bears S.12°W., 64 lks. dist., mkd. T23S R6W S26 BT.
A Fir 10" dia., bears N.15°W., 40 lks. dist., mkd. T23S R6W S23 BT.

BLM Resurvey - James E Jelley, Wayne L. Rogers, and Lance J. Bishop, Cadastral Surveyors Under Group # 1098 - Surveyed June 1982/Nov. 1983 (DCSO records Vol. 46 Page(s) 17729-30)

The Sec. cor., monumented with an iron post, 2" dia., firmly set, projecting 12" above ground, with brass cap (properly) mkd:
(Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec. Cor. for 23, 24, 25 and 26

Alias	Description
Alias	Description
Alias	Description
Alias	Description

from which the remaining original bearing tree
A Fir 42" dia., bears East, 80 lks., with fragmentary scribe marks visible on opened blaze. (Record S.90°E.)
and the remains of BTs mkd. by Gould, Gawron and Eggen:
A sawed Fir stump 15" dia., bears N.12°E., 37 lks., no marks visible. (Rec. 33 lks.)
A sawed Fir stump 32" dia., bears S.66°E., 5 lks., with scribe marks R6W S25 visible on open blaze.
A Chinquapin 19" dia., bears S.14°W., 64 lks., with healed blaze. (Rec. S.12°W.)
A root hole bears N.15°W., 40 lks., with a down Fir alongside, 19" dia., with healed blaze.
and new bearing trees
A Fir 6" dia., bears N.77°E., 35 lks, mkd. T23S R6W S24 BT
A Fir 9" dia., bears S.52°E., 65 lks, mkd. T23S R6W S25 BT
A Fir 5" dia., bears N.8°W., 10½ lks., mkd. X BT.

Fd. and Used in BLM Corrective Dependent Resurvey by Wayne L. Rogers; Boyd W. Peterson; Philip G. Griffin; Dale T. Bedell; Cadastral Surveyors; and Robert H. Browning, Surveying Technician - under Group #'s 1266, 1637 and 1688, - surveyed June 1986/August 1995 - (DCSO records Vol 51 Pgs 19467-68)

Fd. & used on BLM corrective and dependent resurvey by Wayne L. Rogers, Cadastral Surveyor & Robert H. Browning, Surveying Technician, under Group #1803 surveyed May/Nov. 1996 - (DCSO records Vol. 52 Page(s) 19959-60)

BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral Surveyor, under Group No. 2308, Surveyed April/July 2010 - (DCSO records Vol. 57 Page(s) 22837)

The cor. of secs. 23, 24, 25, & 26, monumented with an iron post, 2" dia., firmly set, projecting 17" above ground, with a brass cap (properly) mkd.
from which the remains of the original bearing trees
A fir, 48" dia., bears East, 52.8 ft., with scribe mark S visible on an opened blaze.
A decayed fir stump, size indeterminate, bears N.70°W., 30.4 ft., with no marks visible.
and the remains of BTs mkd. by Gould, Gawron, & Eggen
A decayed fir stump, size indeterminate, bears N.12°E., 24.4 ft., with no marks visible.
A decayed fir stump, size indeterminate, bears S.66°E., 3.3 ft., with scribe marks S R6W S25 visible on an open blaze.
A chinquapin snag, 23" dia., bears S.14°W., 42.2 ft., with a healed blaze. continued next page

TOWNSHIP 23 RANGE 06 POINT IDENTIFIER # 600300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 23, 24, 25 and 26

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

A roothole bears N.15°W., 26.4 ft., alongside of which is a down fir snag, size indeterminate, with no marks visible.
and BTs mkd. by Jelley, Rogers, and Bishop in 1982-83
A fir, 12" dia., bears N.77°E., 23.1 ft., with a healed blaze.
A fir, 20" dia., bears S.52°E., 42.9 ft., with a healed blaze.
A fir, 12" dia., bears N.8°W., 6.9 ft., with a healed double blaze.
and a new bearing tree
A fir, 12" dia., bears S.24¾°W., 30.6 ft., mkd. T23S R6W S26 BT.
Corner is located 95 ft. N. of a ravine, course S.65°W.