

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 23 and 24

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by John A. McQuinn, Deputy Surveyor, under Contract #466, dated April 5, 1883 (DCSO records Vol. 6 Page(s) 240)

Set Dogwood post 3 ft. long, 3" sq., 24" in the ground for ¼ sec. cor., mkd. ¼ S on W. face, from which
A Fir 6" dia., bears N.20°E., 23 lks. dist. mkd. ¼ S BT.
A Fir 20" dia., bears West, 71 lks. mkd. ¼ S BT.

BLM resurvey by Otis Gould, Joseph Gawron, and Orville Eggen, Cadastral Surveyors, under Group #244, surveyed June 1943/October 1957 (DCSO records Vol. Page(s) 12662)

Point for the ¼ sec. cor., at proportionate measurement; there is no remaining evidence of the original corner.

Set an iron post, 3 ft. long, 1" dia., 28" in the ground, with brass cap mkd:

T23SR6W

¼

S23|S24

1957

from which

A Fir 8" dia., bears S.56½°E., 45 lks. dist., mkd. ¼ S24 BT.

A Fir 7" dia., bears N.66°W., 52 lks. dist., mkd. ¼ S23 BT

Fd. OK, K.Hoffine, April 1992, M 117-3

BLM corrective and dependent resurvey by Wayne L. Rogers, Cadastral Surveyor & Robert H. Browning, Surveying Technician, under Group #1803 surveyed May/Nov.. 1996 - (DCSO records Vol. 52 Page(s) 19960-1)

The 1/4 sec. cor. of secs. 23 & 24, monumented with an iron post, 1" diam., firmly set, projecting 12" above ground, with brass cap mkd.

T 23 S R 6 W

¼

S 23 | S 24

57

1943

from which the remains of BTs mkd. by Gould, Gawron, & Eggen
A sawed fir stump, 12" diam., bears S.56½°E., 45 lks., with healed blaze.

A fir, 20" diam., bears N.66°W., 52 lks. with healed blaze.

and a new bearing tree

A hemlock, 8" diam., bears N.29°E., 15 lks. mkd. ¼ S24 BT.

continued next page

TOWNSHIP 23 RANGE 06 POINT IDENTIFIER # 600340

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 23 and 24

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral Surveyor, under Group No. 2308, Surveyed April/July 2010 - (DCSO records Vol. 57 Page(s) 22838)

The ¼ sec. cor. of secs. 23 and 24, monumented with an iron post, 1" dia., firmly set, projecting 14" above ground, with a brass cap (properly) mkd.

from which the remains of BTs mkd. by Gould, Gawron, & Eggen
A sawed, decayed fir stump, 12" dia., bears S.56½°E., 29.7 ft., with a healed blaze.

A fir, 28" dia., bears N.66°W., 34.3 ft., with a healed blaze.

and a bearing tree mkd. by Rogers and Browning in 1996

A fir, 13" dia., bears N.29°E., 9.9 ft., with a healed blaze. (Record, hemlock.)