

PRIMARY CORNER DESCRIPTION Sec. Cor. for 13, 14, 23 and 24

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by John A. McQuinn, Deputy Surveyor, under Contract #466, dated April 5, 1883 (DCSO records Vol. 6 Page(s) 2400-01)

Set a Yew post 4 ft. long, 24" in the ground, 4" sq., for cor. to secs. 13, 14, 23 and 24, mkd: T23S S13 on NE.; R6W S24 on SE.; S23 on SW.; and S14 on NW. face, with 3 notches on S. and 1 notch on E. edges., from which
A Fir 48" dia., bears N.40°E., 113 lks mkd T23S R6W S13 BT
A Fir 24" dia., bears S.82°E., 15 lks. mkd T23S R6W S24 BT
A Fir 30" dia., bears S.52°W., 49 lks. mkd T23S R6W S23 BT
A Fir 16" dia., bears N.55°W., 40 lks. mkd T23S R6W S14 BT

BLM resurvey by Otis Gould, Joseph Gawron, and Orville Eggen, Cadastral Surveyors, under Group #244, surveyed June 1943/October 1957 (DCSO records Vol. 30 Page(s) 12663)

The Sec. cor., determined at record bearing and distance from the original remaining bearing trees:
A Fir 50" dia., bears N.60½°E., 113 lks. dist., mkd. BT.
A Fir 36" dia., bears S.45½°W., 49 lks. dist. marks grown over.
A Fir 14" dia., bears N.22½°W., 40 lks. dist., marks grown over.

At the corner point
Set an iron post, 3 ft. long, 2" dia., 27" in the ground, with brass cap mkd:
T23SR6W
S14|S13
S23|S24
1943

from which
A Fir 50" dia., bears N.48°E., 108 lks. dist. mkd. T23S R6W S13 BT.
A Fir 60" dia., bears S.80°E., 75 lks. dist. mkd. T23S R6W S24 BT.

BLM Corrective Dependent Resurvey by Wayne L. Rogers; Boyd W. Peterson; Philip G. Griffin; Dale T. Bedell; Cadastral Surveyors; and Robert H. Browning, Surveying Technician - under Group #'s 1266, 1637 and 1688, - surveyed June 9, 1986/Aug. 22, 1995 - (DCSO records Vol. 51 Page(s) 19480)

The cor. of secs. 13, 14, 23, and 24, monumented with an iron post, 2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap (properly) mkd.
from which the original bearing trees
(Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec. Cor. for 13, 14, 23 and 24

Alias	Description
Alias	Description
Alias	Description
Alias	Description

A fir, 60" dia., bears N. 60½° E., 113 lks. dist., with scribe marks T23 R6 visible on bark blaze.
A fir, 48" dia., bears S. 45½° W., 49 lks. dist., with healed blaze.
A fir, 24" dia., bears N. 22½° W., 40 lks. dist., with scribe marks T 2 visible on opened blaze.
and the remains of BTs mkd. by Gould, Gawron, and Eggen
A fir, 54" dia., bears N. 48° E., 108 lks. dist., with axe marks visible.
A sawed fir stump, 56" dia., bears S. 80° E., 75 lks. dist., with axe marks visible.
and a bearing tree not of record
A hemlock, 17" dia., bears S. 85° E., 5 lks. dist., with healed blaze.

Fd. & used on BLM corrective and dependent resurvey by Wayne L. Rogers, Cadastral Surveyor & Robert H. Browning, Surveying Technician, under Group #1803 surveyed May/Nov.. 1996 - (DCSO records Vol. 52 Page(s) 19961)

BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral Surveyor, under Group No. 2308, Surveyed April/July 2010 - (DCSO records Vol. 57 Page(s) 22839)

The cor. of secs. 13, 14, 23, and 24, monumented with an iron post, 2" dia., firmly set, projecting 2" above ground, with a brass cap (properly) mkd.
from which the remaining original bearing trees
A fir, 65" dia., bears N.57¼°E., 74.6 ft., with scribe marks T23 6 and other fragmentary scribe marks visible on bark.
A fir, 55" dia., bears S.45½°W., 34.3 ft., with a healed blaze.
A fir, 30" dia., bears N.26½°W., 26.4 ft., with no marks visible on a partially healed blaze. (Record, N.22½°W)
and the remains of BTs mkd. by Gould, Gawron, & Eggen
A fir, 56" dia., bears N.45½°E., 71.3 ft., with axe marks visible. (Record, N.48°E.)
A sawed, decayed fir stump, size indeterminate, bears S.80°E., 49.5 ft., with no marks visible.
and a BT mkd. by person(s) unknown, reported by Rogers and Browning in 1996
A hemlock, 20" dia., bears S.85°E., 3.3 ft., with a healed double blaze.
NAD 1983 (CORS 96)
Latitude: 43°33'42.44"N. Longitude: 123°21'59.50"W.