

PRIMARY CORNER DESCRIPTION Sec. Cor. for 11, 12, 13 and 14

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by John A. McQuinn, Deputy Surveyor, under Contract #466, dated April 5, 1883 (DCSO records Vol. 6 Page(s) 2403)

-----

Set Dogwood post 4 ft. long, 4" sq., 24" in the ground for cor. to secs. 11, 12, 13 and 14 mkd. T23S S12 on NE.; R6W S13 on SE.; S14 on SW.; and S11 on NW. face, with 4 notches on S. and 1 notch on E. edge, from which

- A Laurel 12" dia., bears N.12°E., 38 lks. dist. mkd. T23S R6W S12 BT.
- A Laurel 10" dia., bears S.10°E., 20 lks. dist. mkd. T23S R6W S13 BT.
- A Fir 18" dia., bears S.70°W., 8 lks. dist. mkd. T23S R6W S14 BT.
- A Maple 4" dia., bears N.75°W., 20 lks. dist. mkd. T23S R6W S11 BT.

BLM resurvey by Otis Gould, Joseph Gawron, and Orville Eggen, Cadastral Surveyors, under Group #244, surveyed June 1943/October 1957 (DCSO records Vol. 30 Page(s) 12665)

-----

Point for the sec. cor., at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post 30" long, 2" dia., 27" in the ground, with brass cap mkd:

T23SR6W  
S11 | S12  
S14 | S13  
1957

from which

- A Fir 20" dia., bears N.82°E., 12 lks. dist. mkd. T23S R6W S12 BT.
- A Fir 24" dia., bears S.20°E., 227 lks. dist. mkd. T23S R6W S13 BT.
- A Fir 40" dia., bears S.9¼°W., 349 lks. dist. mkd. T23S R6W S14 BT.
- A Fir 8" dia., bears N.32½°W., 300 lks. dist. mkd. T23S R6W S11 BT.

BLM corrective and dependent resurvey by Wayne L. Rogers, Cadastral Surveyor & Robert H. Browning, Surveying Technician, under Group #1803 surveyed May/Nov. 1996 - (DCSO records Vol. 52 Page(s) 19962-3)

-----

The cor. of secs. 11, 12, 13, & 14, monumented with an iron post, 2½" diam., firmly set, projecting 10" above ground, with brass cap mkd.

continued next page

TOWNSHIP 23 RANGE 06 POINT IDENTIFIER # 600500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 11, 12, 13 and 14

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

T 23 S R 6 W  
S 11 | S 12  
S 14 | S 13  
1957

from which the remains of BTs mkd. by Gould, Gawron, & Eggen  
A fir, 30" diam., bears N.63°E., 119 lks., with  
fragmentary scribe marks visible on opened blaze.  
(Rec. N.82°E., 12 lks.)  
A fir, 26" diam., bears S.18½°E., 228½ lks., with healed  
double blaze. (Record, S.20°E., 227 lks.)  
A sawed fir stump, 48" diam., bears S.15°W., 353 lks., no  
marks visible. (Record, S.9¼°W., 349 lks.)  
A fir, 25" diam., bears N.32½°W., 302 lks., with  
fragmentary scribe marks visible on opened blaze.  
(Record 300 lks.)  
and a new bearing tree  
A fir, 10" diam., bears S.70½°W., 28 lks., mkd. T23S R6W  
S14 BT.

Ken Hoffine - For: Juniper Properties LLC - 6/2015 - C.S.  
File 65/88-15

-----  
Found - 1957 BLM brass cap as per BLM line notes page  
19963-19964.  
30" D.Fir bears N.82½°E., 78.85 ft (1957 rec  
N.82°E., 78.54 ft). Healed face and tag.  
30" D.Fir bears S.18½°E., 150.81 ft as per record.  
Healed face and tag.  
40" D.Fir bears N.32½°W., 199.32 ft as per record  
healed face and tag.  
10" D.Fir blow down (record S.70½°W., 18.48 ft)  
New - 21" D.Fir bears N.13½°W., 51.5 ft we scribe T23S R6W  
S11 BT & TAG.  
18" D.Fir bears S.23°E., 48.7 ft we scribe T23S R6W  
S13 BT & tag.  
Did not locate 48" sawed fir stump (record bears  
S.15°W., 232.98 ft).