

PRIMARY CORNER DESCRIPTION Sec. Cor. for 1, 2, 11 and 12

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by John A. McQuinn, Deputy Surveyor, under Contract #466, dated April 5, 1883 (DCSO records Vol. 30 Page(s) 2405)

Set a Yew post 4 ft. long, 4" sq., 24" in the ground for cor. to secs. 1, 2, 11 and 12, mkd. T23S S1 on NE.; R6W S12 on SE.; S11 on SW.; and S2 on NW. faces, with 5 notches on S. and 1 notch on E. edges, from which

- A Cedar 20" dia., bears N.50°E., 62 lks. dist. mkd. T23S R6W S1 BT.
- A Fir 30" dia., bears S.21°E., 16 lks. dist. mkd. T23S R6W S12 BT.
- A Hemlock 8" dia., bears S.19°W., 72 lks. dist. mkd. T23S R6W S11 BT.
- A Fir 36" dia., bears N.10°W., 60 lks. dist. mkd. T23S R6W S2 BT.

O.F. Thiel, Co. Surveyor of Douglas Co. - Feb. 1934 - C.S. File 61/5-7

I went to what was supposed to be the SW corner of section 1, found a Cedar tree 36" dia. mkd. on the SW. side "Tp.23 S.R.6W., no other marks on tree - and Set a Cedar post as per copy of govt. field notes which is as follows:

- Cedar 20" dia. N.50°E., 62 lks.
- Fir 30" dia. S.21°E., 16 lks.
- Hemlock 8" dia., S.19°W., 72 lks.
- Fir 36" dia., N.10°W., 60 lks.

The only tree found is the Cedar - The NW tree, a Cedar snag badly burned. There was some indication of the SE tree and no indication of the SW tree as described in field notes.

BLM resurvey by Otis Gould, Joseph Gawron, and Orville Eggen, Cadastral Surveyors, under Group #244, surveyed June 1943/October 1957 (DCSO records Vol. 30 Page(s) 12666-67)

Point for the sec. cor., determined at record bearings and distances to two of the remaining bearing trees:

- A Cedar 38" dia., bears N.50°E., 62 lks.. mkd. T23S R6.
- A snag, 36" dia. bears N.10°W. 60 lks. w/marks burned off

At the corner point
Set an iron post, 3 ft. long, 2" dia., 27" in the ground, with brass cap mkd:

T23SR6W	
S 2	S 1
S11	S12

from which
1943

- A Fir 24" dia., bears N.23¼°E., 46 lks. dist. mkd. T23S R6W S1 BT.

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec. Cor. for 1, 2, 11 and 12

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

- A Fir 18" dia., bears S.35°E., 273 lks. dist. mkd. T23S R6W S12 BT.
- A Fir 8" dia., bears S.62°W., 37 lks. mkd. T23S R6W S11 BT.
- A Fir 30" dia. bears N.33°W., 98 lks. mkd. T23S R6W S2 BT.


Survey by Ken Hoffine - For: Lone Rock Timber Co. - March 1990 - C.S. File 63/104-49

-
- Found - Corner is an iron post with brass cap, BLM 1943.
- 15" D.Fir with visible scribing and BLM BT tag that reads T23S R6W Sec. 12, dist. 20 lks. bearing N.59 3/4°W. No record.
 - 35" Cedar snag with no visible scars and a BLM BT tag that reads T23S R6W Sec. 1, dist. 62 lks. bearing S.49½°W. (Orig. BT)
 - 38" D.Fir stump that has been tinned and treated with a BLM BT tag that reads T23S R6W Sec. 1, dist. 46 lks. bearing S.23½°W. (1943 BLM BT)
 - 49" D.Fir well healed face and BLM BT tag that reads T23S R6W Sec. 2, dist. 98 lks. bearing S.27½°E. (1943 BLM BT)
 - 38" D.Fir well healed face and BLM BT tag that reads T23S R6W Sec. 12, dist. 283 lks. bearing N.25½°W., (Rec. 273 lks. S.35°E.)

We paint faces and wrote BT on trunks of all BTs with fluorescent orange paint. Corner sets on bench approx. 80 ft. North and approx. 120 ft. West of gravel road.

BLM Corrective Dependent Resurvey by Wayne L. Rogers; Boyd W. Peterson; Philip G. Griffin; Dale T. Bedell; Cadastral Surveyors; and Robert H. Browning, Surveying Technician - under Group #'s 1266, 1637 and 1688, - surveyed June 9, 1986/August 22, 1995 - (DCSO records Vol. 51 Page(s) 19470-71)

The Sec. cor. monumented with an iron post, 2 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.



from which the remains of an original bearing tree

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec. Cor. for 1, 2, 11 and 12


Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A cedar snag, 44 ins. diam., bears N. 50° E., 62 lks. dist., no marks visible.
 and bearing trees mkd. by Gould, Gawron, and Eggen
 A fir, 40 ins. diam., bears N. 23¼° E., 46 lks. dist., with healed blaze.
 A fir, 39 ins. diam., bears S. 25½° E., 283 lks. dist., with healed double blaze. (Record, S.35°E., 273 lks.)
 A fir, 37 ins. diam., bears S. 62° W., 136 lks. dist., with healed blaze. (Record, 37 lks.)
 A fir, 50 ins. diam., bears N. 27½° W., 98 lks. dist., with healed blaze. (Record, N. 33° W.)
 and a new bearing tree
 A fir, 14 ins. diam., bears S. 59 3/4° E., 20 lks. dist., mkd. T23S R6W S12 BT.

Fd. Ok by L. Roberts, 8/97 - M 127-43

BLM corrective and dependent resurvey by Wayne L. Rogers, Cadastral Surveyor & Robert H. Browning, Surveying Technician, under Group #1803 surveyed May/Nov.. 1996 - (DCSO records Vol. 52 Page(s) 19965-6)

 The cor. of secs. 1, 2, 11, & 12, monumented with an iron post, 2" diam., firmly set, projecting 10" above ground, with brass cap mkd.



from which the remains of an original bearing tree
 A cedar snag, 32" diam., bears N.50°E., 62 lks., with healed blaze.
 and the remains of BTs mkd. by Gould, Gawron, & Eggen
 A sawed fir stump, 39" diam., bears N.23¼°E., 46 lks., with healed blaze, and covered with tin cap.
 A sawed fir stump, 39" diam., bears S.25½°E., 274½ lks., with healed blaze. (Record, 283 lks.)
 A fir, 41" diam., bears S.62°W., 136 lks., with a healed blaze.
 A fir, 52" diam., bears N.27½°W., 98 lks., with a healed blaze.
 and a bearing tree mkd. by Peterson
 A fir, 17" diam., bears S.59 3/4°E., 20 lks., with a healed blaze.
 and a bearing tree mkd. by person(s) unknown
 A fir, 14" diam., bears S.67 3/4°W., 10 lks., with scribe marks S11 visible on partially healed blaze.
 No new trees available in the NE. quadrant.