

TOWNSHIP 23 RANGE 06 POINT IDENTIFIER # 600640

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 1 and 2

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by John A. McQuinn, Deputy Surveyor, under Contract #466, dated April 5, 1883 (DCSO records Vol. 6 Page(s) 2407)

Set Dogwood post 3 ft. long, 3" sq., 24" in the ground for ¼ sec. cor. mkd. ¼ on W. face, from which
A Hemlock 20" dia., bears N.5°E., 14 lks. dist. mkd. ¼ S BT.
A Maple 6" dia., bears N.10°W., 11 lks. dist. mkd. ¼ S BT.

BLM resurvey by Otis Gould, Joseph Gawron, and Orville Eggen, Cadastral Surveyors, under Group #244, surveyed June 1943/October 1957 (DCSO records Vol. 30 Page(s) 12668)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 3 ft. long, 1" dia., 27" in the ground, with brass cap mkd:
$$\begin{array}{c} \frac{1}{4} \\ S 2 | S 1 \\ 1943 \end{array}$$

from which
A Fir 14" dia., bears N.64°E., 57 lks. dist. mkd. ¼ S1 BT.
A Cedar 16" dia., bears N.80°W., 7 lks. dist. mkd. ¼ S2 BT.

BLM Corrective Dependent Resurvey by Wayne L. Rogers; Boyd W. Peterson; Philip G. Griffin; Dale T. Bedell; Cadastral Surveyors; and Robert H. Browning, Surveying Technician - under Group #'s 1266, 1637 and 1688, - surveyed June 9, 1986/August 22, 1995 - (DCSO records Vol. 51 Page(s) 19472)

The ¼ sec. cor. monumented with an iron post, 2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.
$$\begin{array}{c} \frac{1}{4} \\ S2 | S1 \\ 1943 \end{array}$$

from which the remains of bearing trees mkd. by Gould, Gawron, and Eggen
A sawed fir stump, 36 ins. diam., bears N. 64° E., 52 lks. dist., with healed blaze. (Record, 57 lks.)
A cedar, 32 ins. diam., bears N. 80° W., 7 lks. dist., with healed blaze.
and a new bearing tree
A fir, 10 ins. diam., bears S. 17 ¾° E., 26 lks. dist., mkd. ¼ S1 BT.

Fd. Ok by L.Roberts, 8/97 - M 127-43 continued next page

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 1 and 2

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

Dan Saily- For: Lone Rock - Crew: Brett Ragon, Ignacio Roman & Trevor Clemo - 1/9/2024 - C.S. File 65/113-26

-
- Found - 1943 GLO brass cap (properly mkd) and iron pipe.
41" R.Cedar BLM tag and well healed face fd at record (N.80°W., 4.62')
 - 18" W.Fir with BLM tag and well healed face bears S.14¾°E., 17.4' Record [S.17¾°(E) 17.16']
 - New - 20" W.Fir bears S.3°E., 20.3', we tag and scribe X BT
 - 10" D.Fir bears N.2°W., 27.0' we tag and scribe ¼ S2 BT

Note - Bearing basis: 1995 BLM survey which is based on a solar observation.
FD 1986 BLM brass cap and iron pipe as per 1995 BLM record VOL. 51 PG 19520 the top of the monument is at ground level. The monument lies on flat ground. We ran a random traverse from the ¼ corner of secs 1 and 2, through the center west 1/16 and the fd iron rods from M49-60 to the center ¼ of sec 1 and checked it against record distance. BTs were measured with a TRIMBLE C5 TOTAL STATION to an aluminum nail at side center for distance and at center face for bearings.

*NOTES - We were unable to locate two of the record Bentz iron rods from M49-60 along the un-named rock road. Therefore we compute the record inverse from M49-60 between the two found iron rods and show it hereon compared to our measured distance. There appears to be a record distance of 43.51' between two of Bentz iron rods which does not to correlate with the other record distances between the iron rods along the road.