

PRIMARY CORNER DESCRIPTION Standard Cor. for Secs. 1 & 2 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

<p>GLO survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 4 Page(s) 1427)</p> <p>-----</p> <p>Set standard cor. to secs. 1 and 2, from which  A Fir 8" dia., bears S.40°E., 19 lks. dist.  A Fir 10" dia., bears S.15°W., 11 lks. dist.</p>																				
<p>O.F. Thiel, Ex-County Surveyor of Douglas Co. - Feb. 1934 - C.S. File 61/5</p> <p>-----</p> <p>I found the SE bearing tree standing and properly marked. SW tree gone.  Marked - A new tree, a Fir 22" dia., bears S.14°W., 32 lks.</p>																				
<p>BLM resurvey by Otis Gould, Joseph Gawron, and Orville Eggen, Cadastral Surveyors, under Group #244, surveyed June 1943/October 1957 (DCSO records Vol. 30 Page(s) 12624-25)</p> <p>-----</p> <p>The standard cor. of secs. 1 and 2, determined at record bearing and distance from the only remaining original bearing tree:  A Fir snag, 24" dia., bears S.40°E., 19 lks. dist., mkd. S1 SC T23S R6W BT.  At the corner point  Set an iron post, 3 ft. long, 2" dia., 27" in the ground, with brass cap mkd:</p> <div style="text-align: center;"> <table border="0"> <tr><td>S</td><td>2</td><td> </td><td>S</td><td>1</td></tr> <tr><td colspan="5">T23SR6W</td></tr> <tr><td colspan="5">S C</td></tr> <tr><td colspan="5">1943</td></tr> </table> </div> <p>from which  A Fir 48" dia., bears S.26½°E., 109 lks. dist., mkd. T23S R6W S1 SC BT.  A Fir 54" dia., bears S.67°W., 203 lks. dist., mkd. T23S R6W S2 SC BT.</p>	S	2		S	1	T23SR6W					S C					1943				
S	2		S	1																
T23SR6W																				
S C																				
1943																				
<p>Douglas Co. Surveyors Office - Milo Godfrey, Deputy - Wm. Stoffel &amp; M Stone, crew - Feb. 26, 1964 - C.S. File 49/143-97</p> <p>-----</p> <p>Found - GLO brass cap set in 1943.  48" Fir S.13½°E., (not S.26½°E.) 71.9 ft., very plain axe scar.  54" Fir S.67°W., 134.0 ft., uprooted and down.  New BTs -12" W.Fir S.62°W., 27.0 ft. mkd. T23S R6W S2 CS BT  8" W.Fir S.66°E., 14.7 ft. mkd. T23S R6W S1 CS BT.</p>																				
<p>Fd. OK, Aug. 1994, K. Hoffine, M 120-79</p>																				

TOWNSHIP 23 RANGE 06 POINT IDENTIFIER # 600700

PRIMARY CORNER DESCRIPTION Standard cor. for Secs. 1 and 2 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Fd. and used in BLM Corrective Dependent Resurvey by Wayne L. Rogers; Boyd W. Peterson; Philip G. Griffin; Dale T. Bedell; Cadastral Surveyors; and Robert H. Browning, Surveying Technician - under Group #'s 1266, 1637 and 1688, - surveyed June 9, 1986/August 22, 1995 - (DCSO records Vol. 51 Page(s) 19447-48)

Fd. & used on BLM corrective and dependent resurvey by Wayne L. Rogers, Cadastral Surveyor & Robert H. Browning, Surveying Technician, under Group #1803 surveyed May/Nov.. 1996 - (DCSO records Vol. 52 Page(s) 19957)