

TOWNSHIP 23 RANGE 06 POINT IDENTIFIER # 629700

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. Sec. 36 only, T22-6

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 4 Page(s) 1429)

Set ¼ sec. post, C. C., from which
A Fir 16" dia., bears N.10°E., 3 lks. dist.
A Laurel 18" dia., bears N.45°W., 25 lks. dist.

BLM resurvey by Otis Gould, Joseph Gawron, and Orville Eggen, Cadastral Surveyors, under Group #244, surveyed June 1943/October 1957 (DCSO records Vol. 30 Page(s) 12624)

The ¼ sec. cor. of sec. 36 only, T22S R6W, determined at record bearing and distance from the original bearing trees:
A Fir 48" dia., bears N.10°E., 3 lks. dist., mkd. ¼ with other marks grown over.
A Laurel partly dead, 20" dia., bears N.45°W., 23 lks. dist., marks rotted off.

At the corner point
Set an iron post, 3 ft. long, 1" dia., 27" in the ground, with brass cap mkd:
¼ S 36
1943

from which
A Fir 12" dia., bears N.57°W., 102 lks. dist., mkd. ¼ S36 BT.

Survey by Ken Hoffine, L.S. 2291 - For: Lone Rock Timber Co. - Aug 1994 - M 120-79

Found - 2½" GLO Brass Cap 2 ft. below ground. Brass Cap is bent approximately 0.3 ft. NE.
1½" I.P. bears N.49°E., 1.9 ft.. Orig. BT to I.P. bears N.10°E., 2.0 ft., to chopped out face.
46" D.Fir, stump, bears N.27°E., 4.8 ft., to face chopped out, scribing visible.
20" D.Fir, stump, bears N.54°W., 68.0 ft., scribing visible.
18" D.Fir, bears S.69°E., 18.5 ft., I tagged & scribed ¼ S36 BT.
Corner lies on east edge of road grade fill slope.