

TOWNSHIP 23 RANGE 06 POINT IDENTIFIER # 640100

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 36; Sec. 1, T24-6

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Robert Elder and Henry Gile, Deputy Surveyors, under Contract #31 dated April 7, 1853 (DCSO records Vol. 6 Page(s) 2387)

-----  
Set ¼ sec. post, from which  
A Laurel 6" dia., bears S.51°W., 26 lks.  
A Laurel 10" dia., bears N.39°E., 10 lks.  
A Fir 30" dia., bears (?) (?)

BLM resurvey by Otis Gould, Joseph Gawron, and Orville Eggen, Cadastral Surveyors, under Group #244, surveyed June 1943/October 1957 (DCSO records Vol. 30 Page(s) 12642)

-----  
Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.  
Set an Iron post, 3 ft. long, 1" dia., 27" in the ground, with brass cap mkd:  
$$\frac{1}{4} \frac{S 36}{S 1}$$
1943

from which  
A Fir 12" dia., bears N.76°W., 49 lks. dist., mkd. ¼ S36 BT.  
A Fir 48" dia., bears S.10°E., 147 lks. dist., mkd. ¼ S1 BT

Fd. OK, K. Hoffine, July 1993, M 117-52

Found OK by D. Edwards, May 2002 - M140-13