

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 25 and 36

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #310, dated Nov. 30, 1878 (DCSO records Vol. 6 Page(s) 2396)

Set 1/4 sec. post, from which
A Laurel 24" dia., bears N.46 1/2°W., 28 lks.
A B.Oak 18" dia., bears S.82°E., 116 lks.

BLM resurvey by Otis Gould, Joseph Gawron, and Orville Eggen, Cadastral Surveyors, under Group #244, surveyed June 1943/October 1957 (DCSO records Vol. 30 Page(s) 12659)

The 1/4 sec. cor., determined at record bearing and distance from the original bearing trees:
A B.Oak 30" dia., bears S.82°E., 116 lks. dist., with chopped blaze.
A Madrone 34" dia., bears N.46 1/2°W., 28 lks. dist. mkd. 1/4 S on opened blaze.

At the corner point
Set an iron post, 3 ft. long, 1" dia., 27" in the ground, with brass cap mkd:
1/4 S 25
S 36
1957

from which
A Chinquapin 7" dia., bears N.15 1/2°W., 50 lks. dist. mkd. 1/4 S25 BT.
A Fir 9" dia., bears S.23°W., 19 lks. dist. mkd. 1/4 S36 BT

Fd. and Used in BLM Corrective Dependent Resurvey by Wayne L. Rogers; Boyd W. Peterson; Philip G. Griffin; Dale T. Bedell; Cadastral Surveyors; and Robert H. Browning, Surveying Technician - under Group #'s 1266, 1637 and 1688, - surveyed June 9, 1986/August 22, 1995 - (DCSO records Vol. 51 Page(s) 19466)