

TOWNSHIP 23 RANGE 06 POINT IDENTIFIER # 640300

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 24 and 25

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by John A. McQuinn, Deputy Surveyor, under Contract #466, dated April 5, 1883 (DCSO records Vol. 6 Page(s) 2399-2400)

Set Fir post 3 ft. long, 3" sq., 24" in the ground for ¼ sec. cor., mkd. ¼ S on N. face, from which
A Fir 6" dia., bears N.31°E., 22 lks. dist. mkd. ¼ S BT.
A Fir 8" dia., bears S.29°W., 58 lks. dist. mkd. ¼ S BT.

BLM resurvey by Otis Gould, Joseph Gawron, and Orville Eggen, Cadastral Surveyors, under Group #244, surveyed June 1943/October 1957 (DCSO records Vol. 30 Page(s) 12662)

Point for the ¼ sec. cor., at proportionate measurement; there is no remaining evidence of the original corner.
Set an iron post, 30" long, 2" dia., 24" in the ground, with brass cap mkd:

T23SR6W
 S 24
¼ S 25
 1957

from which
A Maple 10" dia., bears N.26½°E., 13 lks. dist., mkd. ¼ S24 BT.
A Maple 8" dia., bears S.71°W., 82 lks. dist., mkd. ¼ S25 BT.

Fd. and Used in BLM Corrective Dependent Resurvey by Wayne L. Rogers; Boyd W. Peterson; Philip G. Griffin; Dale T. Bedell; Cadastral Surveyors; and Robert H. Browning, Surveying Technician - under Group #'s 1266, 1637 and 1688, - surveyed June 9, 1986/August 22, 1995 - (DCSO records Vol. 51 Page(s) 19467)