

TOWNSHIP 23 RANGE 06 POINT IDENTIFIER # 640340

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. for Section 24

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Wilford N. Haines - For: Yoncalla Lumber Co. - August 1961 -
M 23-33

Drove nail in windfall.
Scribed -16" Fir S.68°E., 30.5 ft.
5" Fir S.9°W., 22.2 ft.
Drove 1" x 36" T-Iron 1.0 ft. N.1°01'W., of nail.
E-W centerline calculation from transit and chain traverse.
N-S centerline by triangulation. No closure was made to
either line.

Ken Hoffine - For: Lone Rock Timber Co. - June 1990 - C.S.
File 63/104-58

Found - Corner is a Haines T-Iron 1.5 ft. above ground, 1.0
ft. N.1°W. of nail in rotten log for true corner
position.
20" D.Fir bears S.9°W., 22.2 ft. well healed face
and BT tag.
32" D.Fir bears S.68°E., 30.5 ft. well healed face
and BT tag.
Put metal fence post in at true corner location 1.0 ft.
S.1°E., of Haines T-Iron.
Painted faces and wrote BT on tree trunks of BTs with
fluorescent orange paint. Corner lies (?) of small
northwesterly side ridge, just West of very steep slope
leading to flat ridge top with old dirt logging road.