

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 12 and 13

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by John A. McQuinn, Deputy Surveyor, under Contract #466, dated April 5, 1883 (DCSO records Vol. 6 Page(s) 2404)

-----  
Set a Cedar post 3 ft. long, 3" sq., 24" in the ground for ¼ sec. cor., mkd. ¼ S on the N. face, from which  
A Fir 20" dia., bears N.13°W., 22 lks. dist. mkd. ¼ S BT.  
A Hemlock 8" dia., bears S.25°W., 15 lks. dist. mkd. ¼ S BT.

BLM resurvey by Otis Gould, Joseph Gawron, and Orville Eggen, Cadastral Surveyors, under Group #244, surveyed June 1943/October 1957 (DCSO records Vol. 30 Page(s) 12665-66)

-----  
Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.  
Set an iron post, 3 ft. long, 1" dia., 27" in the ground, with brass cap mkd:  
 $\frac{1}{4} \begin{matrix} S 12 \\ S 13 \end{matrix}$   
1943

from which  
A Cedar 13" dia., bears N.2°W., 101 lks. mkd. ¼ S12 BT.  
A Fir 9" dia., bears S.41°W., 19 lks. mkd. ¼ S13 BT.

Survey by Ken Hoffine - For: Lone Rock Timber Co. - March 1990 - C.S. File 63/104-50

-----  
Found - Corner is an iron post with 2½" brass cap in good condition. BLM 1943  
22" D.Fir bears S.37°W., 11.5 ft. well healed face. Put up a BT tag. (BLM record is S.41°W., 19 lks.)  
13" Western Red Cedar bears N.55°E., 16.0 ft. Put up a Lone Rock Timber location tag. (BT not of record)  
We painted faces and wrote BT on trunk of all BTs with fluorescent orange paint. Corner lies on 50% East slope near top of spur ridge approx. 500 ft. South of road and 400 ft. West of creek.

Fd. & used on BLM corrective and dependent resurvey by Wayne L. Rogers, Cadastral Surveyor & Robert H. Browning, Surveying Technician, under Group #1803 surveyed May/Nov.. 1996 - (DCSO records Vol. 52 Page(s) 19964)

FD BC by D. Edwards, 4/2012 - M163-72  
Fd BC & NE & SW BTs by K Hoffine, C.S. File 65/88-15, 6/2015