

PRIMARY CORNER DESCRIPTION No. 1/4 Cor. Section 1 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 4 Page(s) 1427)

Set Standard ¼ sec. post, from which
A Maple 6" dia., bears S.23°W., 14 lks. dist.
A Fir 6" dia., bears S.68°E., 63 lks. dist.

BLM resurvey by Otis Gould, Joseph Gawron, and Orville Eggen, Cadastral Surveyors, under Group #244, surveyed June 1943/October 1957 (DCSO records Vol. 30 Page(s) 12623-24)

The standard ¼ sec. cor. of sec. 1, determined at record bearing and distance from the only remaining bearing tree:
A Fir 38" dia., bears S.68°E., 63 lks. dist., mkd. BT.
At the corner point
Set an iron post, 3 ft. long, 1" dia., 27" in the ground, with brass cap mkd:

¼ S 1
S C
1943

from which
A Fir 20" dia., bears S.68°E., 106 lks. dist., mkd. ¼ S1
SC BT.
A Fir 24" dia., bears S.65½°W., 36 lks. dist., mkd. ¼ S1
SC BT.

Ken Hoffine, L.S. 2291 - For: Lone Rock Timber Co. - Aug 1994 - M 120-79

Found - GLO Brass Cap set in 1943
Orig. D.Fir, now a 48" rotten stump, bears S.68°E., 42.0 ft., no visible scribing.
28" D.Fir stump, bears S.66°W., 24.4 ft, with visible scribing.
24" D.Fir, decayed stump, bears S.68°E., 70.0 ft. no visible scribing.
8" D.Fir, bears S.20°W., 35.0 ft., w/tag.
Corner lies on flat approximately 50' East from foot of steep hill.

BLM Corrective Dependent Resurvey by Wayne L. Rogers; Boyd W. Peterson; Philip G. Griffin; Dale T. Bedell; Cadastral Surveyors; and Robert H. Browning, Surveying Technician - under Group #'s 1266, 1637 and 1688, - surveyed June 9, 1986/August 22, 1995 - (DCSO records Vol. 51 Page(s) 19446)

From the standard ¼ sec. cor. of sec. 1 only, on the N. bdy.
(Cont. Next Page)

TOWNSHIP 23 RANGE 06 POINT IDENTIFIER # 640700

PRIMARY CORNER DESCRIPTION No. 1/4 Cor. for Sec. 1 only

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

of the Tp., monumented with an iron post, 2½ ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.

¼ S1
SC
1943

from which the remains of bearing trees mkd. by Gould, Gawron, and Eggen

A sawed fir stump, 25 ins. diam., bears S. 68° E., 106 lks. dist., with healed blaze.

A sawed fir stump, 35 ins. diam., bears S. 65½° W., 36 lks. dist., with healed blaze.

and new bearing trees

A fir, 16 ins. diam., bears S. 44¼° E., 47 lks. dist., mkd. ¼ S1 SC BT.

A fir, 5 ins. diam., bears S. 20¼° W., 53 lks. dist., mkd. X BT.