

PRIMARY CORNER DESCRIPTION Sec. Cor. for 25 & 36; 30 & 31, T23-5

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

Original - Robert Elder and Henry Gile, Deputy Surveyors, under Contract #31 dated April 7, 1853 (DCSO records Vol. 6 Page(s) 2342)

Set post, cor. to secs. 30, 31, 25 and 36, from which
A W.Oak 10" dia., bears N.34°E., 185 lks.
A W.Oak 7" dia., bears N.82°W., 523 lks.
A W.Oak 13" dia., bears S.60°W., 436 lks.
A W.Oak 12" dia., bears S.26°E., 490 lks.

Cor. Fd. and used in GLO survey by Wm. Theil, Contract #310 dated Nov. 1878 - except Theil found 13" W.Oak to be S.6°W., 436 lks., not S.60°W. (DCSO records, Vol. 6 Page 2395)

BLM resurvey by Otis Gould, Joseph Gawron, and Orville Eggen, Cadastral Surveyors, under Group #244, surveyed June 1943/October 1957 (DCSO records Vol. 30 Page(s) 12635-36)

The Sec. Cor., determined at record bearing and distance from the original bearing trees:
An Oak 22" dia., bears N.34°E., 185 lks. dist., marks grown over.
An Oak 14" dia., bears N.82°W., 523 lks. dist., marks grown over.

At the corner point
Set an iron post, 3 ft. long, 2" dia., 27" in the ground, with brass cap mkd:
T23S
R6W R5W
S25 S30
S36 S31
1943

from which
A Fir 5" dia., bears S.23°E., 307 lks. dist., mkd. T23S R5W S31 BT.
An Oak 8" dia., bears S.61°W., 445 lks. dist., mkd. T23S R6W S36 BT.

Fd. OK, July 1993, K. Hoffine, M 117-52

BLM Corrective Dependent Resurvey by Wayne L. Rogers; Boyd W. Peterson; Philip G. Griffin; Dale T. Bedell; Cadastral Surveyors; and Robert H. Browning, Surveying Technician - under Group #'s 1266, 1637 and 1688, - surveyed June 9, 1986/August 22, 1995 - (DCSO records Vol. 51 Page(s) 19454)

The sec. Cor., monumented with an iron post, 2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. (Cont. Next Page)

TOWNSHIP 23 RANGE 06 POINT IDENTIFIER # 700200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 25 & 36; 30 & 31, T23-5

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

T23S
R6W R5W
S25 S30
S36 S31
1943

from which the remains of an original bearing tree
An oak snag, 24 ins. diam., bears N. 34° E., 185 lks.
dist., no marks visible.
and bearing trees mkd. by Gould, Gawron, and Eggen
A fir, 20 ins. diam., bears S. 25° E., 303 lks. dist.,
with healed blaze. (Record, S. 23° E., 307 lks.)
An oak, 24 ins. diam., bears S. 61° W., 445 lks. dist.,
with healed blaze.
and new bearing trees
An oak, 10 ins. diam., bears N. 51° E., 21 lks. dist.,
mkd. T23S R5W S30 BT.
A fir, 11 ins. diam., bears N. 27° W., 97 lks. dist., mkd.
T23S R6W S25 BT.