



TOWNSHIP 23 RANGE 06 POINT IDENTIFIER # 700340

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 24; & 19 of T23-5

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Painted face and wrote BT on tree trunk of BTs with flourescent orange paint. Corner lies on steep West slope approx. 2½ chs. West of gravel road, 15-20 year old timber West and a clearcut to the East.

BLM Corrective Dependent Resurvey by Wayne L. Rogers; Boyd W. Peterson; Philip G. Griffin; Dale T. Bedell; Cadastral Surveyors; and Robert H. Browning, Surveying Technician - under Group #'s 1266, 1637 and 1688, - surveyed June 9, 1986/August 22, 1995 - (DCSO records Vol. 51 Page(s) 19457)

-----  
The 1/4 sec. cor., monumented with an iron post, 1 in. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.

1/4  
S 24 | S 19  
1943

from which the remains of bearing trees mkd. by Gould, Gawron, and Eggen

A sawed fir stump, 27 ins. diam., bears N. 72 3/4° E., 61 lks. dist., with healed blaze. (Rec. S. 33° E., 67 lks.)

A sawed fir stump, 38 ins. diam., bears N. 68½° W., 141 lks. dist., with healed blaze. (Rec. N.70 W., 144 lks.)

and new bearing trees

A fir, 10 ins. diam., bears S. 21 3/4° E., 14 lks. dist., mkd. 1/4 S19 BT.

A fir, 12 ins. diam., bears N. 66° W., 27 lks. dist., mkd. 1/4 S24 BT.

From this point, Bureau of Land Management Geodetic Control Station No. EC 41179, at latitude 43° 33' 31.936" N. and longitude 123° 23' 27.852" W. (NAD 1927), determined by the NAVSTAR Global Position System, bears N. 84° 31' 10" W., 185.892 chs. dist. (mean bearing and sea level distance), monumented with an aluminum cap set flush with the ground, mkd. EC 41179 GPS 1993 and a triangle.

DCSO-GIS Corner visitation - 1/31/2006 - Typed: 1/11/2011 - C.S. File 67/33-1

-----  
Monument - 2½" BC/IP. Comment - 2 live BTs

Fd. Ok by Ken Hoffine, 1/2006 - M149-61

continued next page

TOWNSHIP 23 RANGE 06 POINT IDENTIFIER # 700340

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 24; & 19, T23-5

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

BLM Dependent Resurvey by A Bert Skeesick, Cadastral Surveyor and Robert H Browning, Survey Tech, Under Group No. 2315, Surveyed May/June 2010 - DCSO records Vol. 57 Page(s) 22774

-----

The ¼ sec. cor. of secs. 19 & 24, on the W. bdy. of the Tp., ...monumented with an iron post, 1" dia., firmly set, projecting 5" above the ground, with brass cap (properly) mkd from which the remains of bearing trees mkd. by Gould, Gawron, and Eggen, reported by Rogers, et al

A sawed fir stump, 27" dia., bears N.72¾°E., 40.3 ft., with scribe marks S 19 visible on a decayed open face. and bearing trees mkd. by Rogers, et al

A fir, 13" dia., bears S.21¾°E., 9.2 ft., with a healed blaze.

A fir, 16" dia., bears N.66°W., 17.8 ft., with a healed blaze.