

TOWNSHIP 23 RANGE 06 POINT IDENTIFIER # 700600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 1 & 12; 6 & 7, T23-5

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Robert Elder and Henry Gile, Deputy Surveyors, under Contract #31 dated April 7, 1853 (DCSO records Vol. 6 Page(s) 2339)

-----  
Set post, cor. to secs. 6, 7, 1 and 12, from which  
A Fir 16" dia., bears S.10°E., 32 lks.  
A Fir 12" dia., bears S.45°W., 68 lks.  
A Fir 20" dia., bears N.5°W., 22 lks.  
A Fir 18" dia., bears N.40°E., 41 lks.

Cor. Fd. in GLO survey by John McQuinn, under contract #466, dated April 1883 (DCSO records, Vol. 6 Page 2406)

Survey by O.F. Thiel, Ex-County Surveyor of Douglas Co. - Feb. 1934 - C.S. File 61/5

-----  
After considerable investigation, found the old bearing trees, cut in the NE tree, found old marks. NW tree standing but dead, others cut down. Set Cedar Post.

BLM resurvey by Otis Gould, Joseph Gawron, and Orville Eggen, Cadastral Surveyors, under Group #244, surveyed June 1943/October 1957 (DCSO records Vol. 30 Page(s) 12640-41)

-----  
The Sec. cor., determined at record bearing and distance from the remains of the original bearing trees:

A dead Fir 40" dia., bears N.40°E., 41 lks. dist., with marks burned off.  
A Fir stump 24" dia., bears S.10°E., 32 lks. dist., with marks burned off.  
A Fir stump 16" dia., bears S.45°W., 68 lks. dist., mkd. T23S S12 BT.  
A Fir stump, even with the ground, bears N.5°W., 22 lks. dist.

At the corner point

Set an iron post, 3 ft. long, 2" dia., 27" in the ground, with brass cap mkd:

T	23	S			
R	6	W	R	5	W
S	1	S	6		
S12	S	7			
1943					

from which

A Fir 40" dia., bears N.49°E., 49 lks. dist., mkd. T23S R5W S6 BT.

(Cont. Next Page)

TOWNSHIP 23 RANGE 06 POINT IDENTIFIER # 700600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 1 & 12; 6 & 7, T23-5

Alias	Description
Alias	Description
Alias	Description
Alias	Description

A Fir 36" dia., bears S.21°E., 48 lks. dist., mkd. T23S R5W S7 BT.  
A Fir 24" dia., bears S.15½°W., 304 lks. dist., mkd. T23S R6W S12 BT.  
A Cedar 16" dia., bears N.55°W., 72 lks. dist., mkd. T23S R6W S1 BT.

Douglas Co. Surveyors Office - L.E. Monrean, R.B. Kimberling, crew - April 12, 1977 - C.S. File 59/31-24

-----  
Found - 1943 GLO brass cap on 2" pipe (O.D.) 7" above ground, properly mkd.  
24" Fir stump bears S.5°E., (Rec. S.10°E.) 21.1 ft. Blazed and mkd. R5W T23S S7.  
16" Fir stump bears S.45°W., 42.6 ft. (Rec. 44.9 ft.) blazed and mkd. T23S S21 BT.  
Remains of Fir stump, center of root hole bears N.5°W., 14.5 ft.  
D. Fir windfall 41", bears N.49°E., approx. 32.3 ft. to center of root hole, single blaze and mkd. T23S R5W S6 BT.  
D. Fir 36", bears S.21°E., 31.7 ft. with well healed blaze.  
28" Cedar bears N.53½°W., (Rec. N.55°W.) 47.5 ft. with well healed blaze facing N.70°E.  
New BTs -22" Madrone bears S.68°W., 19.4 ft. double blazed and mkd. T23S R6W S12 CS BT.  
11" D. Fir bears N.56°E., 51.0 ft. double blazed and mkd. T23S R5W S6 CS BT.

Fd. OK, April 1990, C.S. File 63/127-19  
Fd. OK, Dec. 1993, D. Baker, M 118-43

Fd. and Used in BLM Corrective Dependent Resurvey by Wayne L. Rogers; Boyd W. Peterson; Philip G. Griffin; Dale T. Bedell; Cadastral Surveyors; and Robert H. Browning, Surveying Technician - under Group #'s 1266, 1637 and 1688, - surveyed June 9, 1986/August 22, 1995 - (DCSO records Vol. 51 Page(s) 19461)

DCSO-GIS Corner visitation - 3/13/2006 - Typed: 1/20/2011 - C.S. File 67/33-1

-----  
Monument - 2½" BC/IP  
Comment - ok; 3 live BTs, 1 snag BT

continued next page

TOWNSHIP 23 RANGE 06 POINT IDENTIFIER # 700600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 1 & 12; 6 & 7, T23-5

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Ken Hoffine - Crew: Gary Angiolet & Ignacio Roman - 6/2017 -  
C.S. File 65/101-51

-----  
Found - 1943 GLO brass cap  
15" D.Fir bears N.54¼°E., 49.3 ft. (Record N.55°E.,  
49.6 ft.) Healed face and tag  
42" D.Fir bears S.20°E., 31.3 ft. (Record S.20°E.,  
31.3 ft.) Healed face and tag  
36" Cedar bears N.54½°W., 47.6 ft. (Record N.54½°W.,  
47.1 ft.) Healed face and tag

New - 13" D.Fir bears S.56¾°W., 37.1 ft. We scribe T23S  
R6W S12 BT and tag tree

Note - We ran a random closed loop traverse beginning at  
the W1/16 corner between sections 6 & 7,  
traversing westerly to the SW corner of sec. 6,  
a 1943 GLO BCIP. We then blazed, painted,  
flagged, and tagged true line. Corner lies on  
West side of ridgetop.