

TOWNSHIP 23 RANGE 06 POINT IDENTIFIER # 700620

PRIMARY CORNER DESCRIPTION So. 1/16 cor. bet. Sec. 1; & 6 of T23-5

| | |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

Survey by V.W. Hosford - For: Roy Harvey - Feb. 1973 - M 48-3

Set 1/2" I.P. and scribed
24" Cedar N.21°E., 25.7 ft.
10" Cedar N.49°W., 6.3 ft.

Survey by Ken Hoffine, LS #2291 - Gary Angiolet, witness -
For: Lone Rock Timber Co. - June 1990 - C.S. File 63/104

Found - Corner is a 1½" Iron post with brass cap. (1986
BLM, no record)
14" Cedar bears N.52°W., 6.3 ft. well healed face
and BLM BT tag.
32" Cedar bears N.19½°E., 25.3 ft. well healed face
and BLM BT tag.

We paint faces and wrote BT on trunk of all BTs with
flourescent orange paint. Corner sits on steep westerly
slope 2 chs. West of bald knob. There is a BLM blazed line
running South, and BLM boundary tags running West from
corner.

BLM Corrective Dependent Resurvey by Wayne L. Rogers; Boyd W.
Peterson; Philip G. Griffin; Dale T. Bedell; Cadastral
Surveyors; and Robert H. Browning, Surveying Technician -
under Group #'s 1266, 1637 and 1688, - surveyed June 9,
1986/August 22, 1995 - (DCSO records Vol. 51 Page(s) 19462)

The S 1/16 sec. cor. of secs. 1 and 6, established by Vernon
W. Hosford, Registered Land Surveyor No. 253, in 1973, and
is accepted as the corner; monumented with an iron rod, 5/8
in. diam., firmly set, projecting 4 ins. above ground, from
which bearing trees mkd. by Hosford:

A cedar, 30 ins. diam., bears N. 19¼° E., 38 lks. dist.,
with healed double blaze.

A cedar, 14 ins. diam., bears N. 52° W., 10 lks. dist.,
with healed double blaze.

At the corner point

Set a stainless steel post, 28 ins. long, 2½ ins. diam.,
25 ins. in the ground, directly over the iron rod, with brass
cap mkd.

S 1/16
S1 S6
1986

Deposit a white "DEEP-1" magnetic marker at the base of the
stainless steel post.