

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Surveys of Donation Land Claims by - Dennis Hathorn, Deputy,  
dated June 8, 1857 - DLC volumes, Page 119-120  
-----

NW. cor. in Sec. 33, Set post, from which  
An Oak 18" dia., bears S.20°W., 336 lks.

Survey by Don E. Garrett - April 15, 1966 - M 33-1  
-----

Found 12" x 12" sandstone, from which  
A 28" Fir bears N.45°E., 7.0 ft. scribed NW. CL. 38.

Douglas Co. Surveyors Office - Stephen Flause, Deputy - T.  
Plouff; S. Means, crew - April 16, 1980 - C.S. File 61/6-27  
-----

Found - Garrett's 12" x 12" sandstone, which when referenced  
out and removed from ground, we find to measure  
14" x 14" x 16". Sandstone is marked with "X" and  
is at corner of fences running E. W. and S.  
Search for but find no evidence of orig. 18" Oak BT.  
A 28" now 30" DBH D.Fir bears N.45°E., 7.0 ft., has  
partially healed double blaze with scribed "D"  
visible.

We perpetuate position of corner at sandstone as accepted by  
Garrett. We reference out sandstone and remove.

Set a 1" x 30" I.P. with brass cap marked:

Douglas County Surveyor  
T 23 S R 7 W  
DLC 38 1980

We place sandstone on South edge of cap. Both cap and stone  
are firmly set and protrude 0.1 ft. from ground.

New BTs- A 12" B.Oak bears N.87°E., 67.0 ft. scribed "NW DLC  
38 CS BT" on a double blaze.

A 24" B.Oak bears S.02°W., 109.9 ft. scribed "NW DLC  
38 CS BT" on a double blaze.

We tag trees with DCSO BT tags.

Douglas Co. Surveyors Office - Randall W. Smith, Deputy -  
Stephen J. Flause - 2/28/2002 - C.S. File 66/32-18  
-----

Found - 1980 DCSO BC/IP protrudes 1" above ground top of  
stone along south edge 1" below ground. Corner  
lies on the south edge of a fence corner, lines  
run E-W+South.

28" now 30" dia., 2½ ft. high D.Fir stump with  
illegible scribing visible, bears N.45°E., 7.0  
ft. (1966)

continued next page

TOWNSHIP 23 RANGE 07 POINT IDENTIFIER # 038020

PRIMARY CORNER DESCRIPTION NW Cor. Johnson Goff DLC #38

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

24" dia., B.Oak now 33" dia., W.Oak with rotted  
blaze we rescribe on a double blaze "NW DLC 38 CS  
BT" bears S.2°W., 109.9 ft. (1980)  
12" dia., B.Oak now 23" dia., W.Oak with a fully  
healed single blaze, bears N.87°E., 67.0 ft.  
(1980)  
New - 19" dia., D.Fir double blazed & scribed "NW DLC 38  
CS BT" bears N.3°W., 70.4 ft.  
19" dia., I.Cedar double blazed & scribed "NW DLC 38  
CS BT" bears N.48°E., 51.0 ft.