

TOWNSHIP 23 RANGE 07 POINT IDENTIFIER # 046070

PRIMARY CORNER DESCRIPTION Int SE Cor Shadrack Hudson DLC #46

Alias 400248 Description Pt on W bdy Sec 27
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Surveys of Donation Land Claims by - Dennis Hathorn, Deputy,
dated June 8, 1857 - DLC Volume, Page 130

Set post interior cor., from which
An Oak 18" dia., bears N.43°W., 42 lks.
An Oak 30" dia., bears N.66°E., 78 lks.

B. B. Irving, Deputy Co. Surveyor - Wit: N.E. Richardson;
W.E. Holcomb; Kausche - Sept. 9, 1929 - Vol. 3 Pg. 299 and
C.S. File 37/6

Set 6" x 6" x 18" sandstone chiseled "Cl. 46 CS" on NW. face,
12" in ground for corner from original BTs. As they are in
good condition, reblazed and rescribed "Cl. 46 CS BT".

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew
Jan. 1966 C.S. File 52/125-43

Found - Piece of sandstone mkd. "Cl 4".
Both original BTs, down & burned, no scribe fd on
these BTs.
18" B.Oak N.30°W. 43.3' opened previously & shows "Int
L DLC 46", lower scar shows up good. (unrec. BT)
Set Brass cap at cor. mkd: County Surveyors Office
T 23 S R 7 W
Int. L DLC 46/-----
1966
New BTs- 24" B.Oak S.15°E. 65.0 ft. mkd. "Int L DLC 46 CS BT"
26" B.Oak S.69°W. 92.1 ft. mkd. "Int L DLC 46 CS BT"
This corner lies at fence corner, fence running N., S., & E.

Douglas Co. Surveyors Office - Randall W. Smith, Deputy -
Stephen J. Flause - 7/30/2002 - C.S. File 66/34-25

Found - 1966 DCSO brass cap/iron pipe at fence corner, fence
lines run N-S & E, protrudes 8" out of ground.
18" B.Oak now 27" dia., W.Oak with a fully healed
single blaze, bears N.28°W., 43.3 ft. (Rec.
N.30°W., 43.3 ft.)
24" now 26" dia., B.Oak with a fully healed double
blaze bears S.11½°E., 64.0 ft. (rec. S.15°E.,
65.0 ft.) 1966
26" now 38" dia. B.Oak w/fully healed single blaze
bears S.71°W. 90.5 ft. (rec. S.69°W. 92.1') 1966
New - 8" dia., W.Oak double blazed & scribed "Int SE DLC
46 CS BT" bears S.40°E., 51.0 ft.
Compass decl. 17¼°E.