

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Surveys of Donation Land Claims by - Dennis Hathorn, Deputy,
dated June 8, 1857 - DLC Volume, Page 131

An Oak 36" dia., SE Cor. from which
A Fir 15" dia., bears N.60°E., 23 lks.

Douglas Co. Surveyors Office - Ben B. Irving, Deputy - Wit:
N.E. Richardson; Kausche - Sept. 1929 - Vol. 3 Pg. 299; C.S.
File 37/6

Found a 60" Oak tree, probably orig. corner as it checks
bearing and distance from sec. line and int. cor. Drove pipe
alongside to NW.
New BTs- 28" Fir bears N.55°W., 59 lks., blazed and scribed
"Cl 46 CS BT"
60" Fir N.35°E., 16 lks., blazed and scribed "C 46
CS BT"

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew
Jan. 1966 C.S. File 52/125-36

Found - 2" I.P., 33" long on NW. side of 60" burned Oak
stump.
60" Fir N.35°E., 10.6 ft., shows "BT" bark scribe in
very poor condition. Now stump.
28" now 36" Fir, N.55°W., 38.9 ft., shows "B", bark
scribe, now stump.
Since corner stump is hollow, We set a brass cap in ground in
center of stump mkd: County Surveyors Office 1966
T23S R7W E SE DLC 46_____/

New BTs- 14" W.Oak N.81°W., 43.8 ft. mkd. E SE DLC 46 CS BT
15" W.Oak N.30°W., 70.7 ft. mkd. E SE DLC 46 CS BT
2" I.P. bears N.28°W., 1.8 ft.

Douglas Co. Surveyors Office - Randall W. Smith, Deputy -
Stephen J. Flause - 7/30/2002 - C.S. File 66/34-27

Condition report
Found - 1966 DCSO brass cap/iron pipe at fence corner, lines
run N-S & W. 1¼" I.D. iron pipe found out of
ground, measured 31" long. (1929)
Orig. Oak corner tree now shallow depression in
ground.
60" dia., 3½ ft. high D.Fir stump no marks found
bears N.35°E., 13.5 ft. to center (1929) rec.
N.35°E., 10.6 ft. dist. hits bark) (OBT rec.
N.60°E., 15.2 ft.)

continued next page

TOWNSHIP 23 RANGE 07 POINT IDENTIFIER # 046080

PRIMARY CORNER DESCRIPTION E SE Cor Shadrack Hudson DLC #46

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

28" now rotted D.Fir bears N.55°W., 38.9 ft. (1929)
14" now 25" dia., W.Oak with a fully healed blaze,
bears N.81°W., 43.8 ft. (1966)
15" now 20" dia., W.Oak with a fully healed double
blaze bears N.30°W., 70.7 ft. (1966)
15" dia., W.Oak double blazed & scribed "ESE DLC 46
CS BT" bears S.24°W., 61.9 ft.
10" dia., D.Fir double blazed & scribed "ESE DLC 46
CS BT" bears S.49°E., 14.3 ft.