

TOWNSHIP 23 RANGE 07 POINT IDENTIFIER # 050020

PRIMARY CORNER DESCRIPTION N NW Cor Levi Grant DLC #50

Alias 051030 Description SW Cor G Snyder DLC #51
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Surveys of Donation Land Claims by - Dennis Hathorn, Deputy,
dated June 8, 1857 - DLC Volume, Page 134 and Page 136

Set stone post 8x10x12 ins., from which
An Oak 12" dia., bears S.80°E., 135 lks.

C.E. Roberts - Dec. 1905 - Vol. 2 Page 284

Set post. Marked new tree. Old bearing tree decayed.
B.Oak 10", S.72½°W., 22½ lks.
W.Oak 8", N.61°W., 22 lks.

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew
Dec. 15, 1965 - C.S. File 52/125-26

Found - 10" now 22" B.Oak S.72½°W., 14.8 ft., shows good
scars, alive and in good condition. Did not open.
8" W.Oak N.61°W., 15.8 ft., recorded as 14.5 ft.
Open and shows "CS" scribe and face is split.
Set Brass cap at cor. mkd: County Surveyors Office
T 23 S R 7
SW DLC 51 |---
1965

New BT - 10" W.Oak N.33°W., 20.8 ft. mkd. SW DLC 51 CS BT.
This corner lies at fence corner, course E., N., and S.

Fd. Co. alum. cap - Sept. 1992 by Beckley - M 119-80

Douglas Co. Surveyors Office - Randall W. Smith, Deputy -
Stephen J. Flause - 7/22/2002 - C.S. File 66/34-15

Found - 1965 DCSO brass cap iron pipe set in concrete at 3
way fence corner protrudes 4" out of ground
stamping on cap orientated SE.
10" now 23" dia., B.Oak w/fully healed blaze, bears
S.77°W., 14.8 ft. (rec. S.72½°W., 14.8 ft.) 1905
8" now double trunked W.Oak with a fully healed
blaze on southerly 16" dia., trunk center of
scribed trunk bears N.61°W., 16.4 ft. (rec.
N.61°W., 15.8 ft.) 1905
10" now 10" dia., W.Oak with a fully healed double
blaze bears N.35°W., 20.8 ft. (rec. N.33°W., 20.8
ft. Brg. hits blaze) 1965
OBT not found.
Compass decl. 17¼°E.