

PRIMARY CORNER DESCRIPTION WC SW Cor. Levi Grant DLC #50

Alias 053060 Description SE Cor. G. Paine DLC #53
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Surveys of Donation Land Claims by - Dennis Hathorn, Deputy,
dated June 8, 1857 - DLC Volume, Page 134-135 and 138

Mark an Oak 15" dia. on right bank of Umpqua River, from
which

An Oak 18" dia., bears N.20°E., 40 lks.

An Oak 15" dia., bears S.88°W., 38 lks.

J.W. Cole, Deputy - Wit: L.H. Smick; Alfred Haines; Warren
Cheever - 2/29/1921 - Vol. 3 Pg 89-90; Field Book 20 Pg 28

Set witness corner N.8°W., 100 ft. of true corner. Set iron
pipe and 4"x4"x40" Oak stake, from which

An Oak 10" dia., bears S.66°E., 27.0 ft.

An Oak 12" dia., bears S.23°30'W., 40.0 ft.

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew
Dec. 1965 - C.S. File 52/125-33

Found - No trace of I.P. as called for by Cole.

10" now 16" W.Oak S.66°E. 27.0 ft. Open & find "CS".

Set Brass cap at wit. cor. mkd: County Surveyors Office

T 23 S R 7 W

W.C. DLC 53 /

Corner 100 ft. S. and E.

1965

New BTs- 20" B.Oak N.5°W., 28.1 ft. mkd. WC DLC 53 CS BT.

10" B.Oak N.62°E., 16.7 ft. mkd. WC DLC 53 CS BT.

This witness corner lies 3.0 ft. West of fence, course N.8°W.

Douglas Co. Surveyors Office - Randall W. Smith, Deputy -
Stephen J. Flause - 6/25/2002 - C.S. File 66/34-13

Found - 1965 DCSO brass cap/iron pipe protruding 6" out of
ground, and tipped over.

1921 3/4" by 29" long iron pipe 7" below ground,
plumb position falls in N'ly running fence line.

1965 DCSO BC/IP set in error bears N.66°W. 3.4 ft

From 1921 position (Vol. 3 pg. 90)

10" now cluster of W.Oak with a previously opened
unhealed blaze on 14" dia., NW'ly trunk center of
Oak cluster bears S.66°E., 27.0 ft. center of
NW'ly trunk S.66°E., 25.3 ft. (1921)

12" now 17" dia., W.Oak with a fully healed blaze
bears S.23½°W., 40.0 ft. (1921)

10" B.Oak now 11" dia, W.Oak with a fully healed
double blaze bears N.53°E., 14.9 ft. (1965)

continued next page

TOWNSHIP 23 RANGE 07 POINT IDENTIFIER # 050050

PRIMARY CORNER DESCRIPTION SW Cor. Levi Grant DLC #50

Alias 053060 Description SE Cor. G. Paine DLC #53

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

20" B.Oak now 25" dia., W.Oak with a fully healed
single blaze, bears N.10½°W., 30.0 ft.

New - 1965 BC/IP removed & a 5/8" by 30" long iron rod
with DCSO plastic cap set at its position flush
with ground.

At plumb position of 1921 IP, 1965 BC/IP is set &
stamping added "RESET 2002" protrudes 10" out of
ground. 1921 IP set along North edge of BC/IP
protrudes 8" out of ground. Cap marked:

COUNTY SURVEYORS OFFICE

T23S

R7W

S8E | WC

100 FT | SE DL

TO COR 53

RESET 2002

1965

Compass decl. 17¼°E.