

TOWNSHIP 23 RANGE 07 POINT IDENTIFIER # 100100

PRIMARY CORNER DESCRIPTION SW Cor. Sec. 31 (SW Tsp Cor.)

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GL0 survey by Thomas H. Hutchinson, Deputy Surveyor, under Contract #60, dated July 19, 1855 - (DCS0 records Vol. 6 Page(s) 2460-61)

-----  
Set post cor. to Tps. 23 and 24 South, ranges 7 and 8 West.  
Also cor. to secs. 31, 36, 1 and 6, from which  
A Fir 22" dia., bears N.80°E., 7 lks. dist.  
A Fir 26" dia., bears S.60°E., 9 lks. dist.  
A Fir 16" dia., bears S.65°W., 59 lks. dist.  
A Fir 14" dia., bears N.28°W., 110 lks. dist.

Corner used in GL0 survey by William Whipple, Deputy Surveyor, under Contract #622, dated June 23, 1893 - Vol. 6 Page 2551)

GL0 survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619, dated June 5, 1893 - (DCS0 records Vol. 8 Page(s) 3224-25)

-----  
The Tp. corner which is a post, 4" sq., 2 ft. above ground marked T23S S31 on NE.; R7W S6 on SE.; T24S S1 on SW.; and R8W S36 on NW. faces, with 6 notches on each edge, from which  
A Fir 22" dia., bears N.80°E., 7 lks. dist. mkd. T23S R7W S31 BT.  
A Fir 26" dia., bears S.60°E., 9 lks. dist. mkd. T24S R7W S6 BT.  
A Fir 16" dia., bears S.65°W., 59 lks. dist. mkd. T24S R8W S1 BT.  
A Fir 14" dia., bears N.28°W., 110 lks. dist., mkd. T23S R8W S36 BT.

I destroy marks on both post and trees referring to Tps. and secs. South of the cor.

Douglas Co. Surveyors Office - James Byron, Deputy - Milo Godfrey; Clete Putnam, crew - Sept. 1960 - C.S. File 49/41-48

-----  
Found - Orig. 16" now 36" Fir S.65°W., 38.9 ft., previously opened, shows good scribing "T24S".  
Orig. NE. and SE. trees, now rotted stumps only.  
Orig. 14" now 30" Fir N.28°W., 72.6 ft., shows good scars.

Set Brass cap at cor. mkd: County Surveyors Office

R T 23 S R  
8 S 36 | S 31 7  
W T 24 S W  
1960

(Cont. Next Page)

TOWNSHIP 23 RANGE 07 POINT IDENTIFIER # 100100

PRIMARY CORNER DESCRIPTION SW Cor. Sec. 31 (SW Tsp. Cor.)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

New BTs- 18" R.Fir bears N.72°E., 62.5 ft. scribed S31 T23S  
R7W CS BT.  
12" R.Fir bears N.63°W., 53.6 ft. scribed S36 T23S  
R8W CS BT.  
Found corner to be East 216 ft. from corner for secs. 6 and  
1, Tsp. 24 Rgs. 7 & 8. (Rec. 215.2 ft.)

Fd. and used in BLM resurvey by C. Albert White and Donald R.  
Beck, Cadastral Surveyors, under Group #515, Surveyed  
June/Oct. 1963 - (DCSO records Vol. 32 Page(s) 13479-80)

Fd. OK, March 1982 by L. Roberts - M 91-74

BLM Dependent resurvey by A. Bert Skeesick, Cadastral  
Surveyor and Robert H. Browning, Survey Tech, under special  
instructions and Group No. 2104, surveyed July 2005/Jan. 2006  
(DCSO records Vol. 57 Page(s) 22402-3)

-----  
The orig. cor. of secs. 31 & 36, T23S Rs 7 & 8 W, established  
by Hutchinson in 1857, remonumented by the Douglas County  
Surveyors Office in 1960, bears N.89°52'34"E., 216.01 ft.,  
monumented with an iron post, 1½" dia., firmly set,  
projecting 15" above ground, with brass cap (properly) mkd.  
from which the remains of the orig. bearing trees  
A decayed fir stump, 30" dia., bears S.65°W., 38.9 ft.,  
with illegible scribe marks visible.  
A fir, 40" dia., bears N.29°W., 75.9 ft., with a healed  
blaze. (Record, 72.6 ft.)  
and bearing tree mkd. by the Douglas County Surveyors Office,  
reported by White and Beck  
A fir, 29" dia., bears N.72°E., 62.7 ft., with a healed  
double blaze.  
and bearing tree mkd. by the Douglas County Surveyors Office,  
not reported by White and Beck  
A fir, 32" dia., bears N.63°W., 53.4 ft., with a healed  
double blaze.

Douglas Co. Surveyors Office - Crew: Stephen Flause & Jeff  
Lorsung- 8/5/2020 (filed 11/3/2022) - C.S. File 67/54-44

-----  
Reported as Fd OK