

TOWNSHIP 23 RANGE 07 POINT IDENTIFIER # 100140

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 31; and 36, T23-8

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Thomas H. Hutchinson, Deputy Surveyor, under Contract #60, dated July 19, 1855 - (DCSO records Vol. 6 Page(s) 2460)

-----  
Set ¼ sec. post, from which  
A Fir 12" dia., bears S.60°E., 25 lks. dist.  
A Fir 30" dia., bears West, 11 lks. dist.

Douglas Co. Surveyors Office - James Byron, Deputy - April 23, 1956 - C.S. File 47/142

-----  
Found old square stake on ground under 3 ft. log, checks bearings and distance to original BT, S.60°E., 16.5 ft., now sng and rotted. Found "BT" scribed at base. The West BT is down and partly burned, no scribing visible, checks bearing and distance to stump.

Set an iron pipe with brass cap at North edge of log mkd:

County Surveyors Office

T 23 S

R8W ¼ 36|31 R7W

1956

New BTs- 12" Fir bears N.37°W., 18.0 ft. scribed ¼ S36 CSBT  
6" Fir bears S.52°E., 16.8 ft. scribed ¼ S31 CSBT.

BLM resurvey by James E. Jelley and Wayne L. Rogers, Cadastral Surveyors, under Group #1102, surveyed July/Aug. 1982 - (DCSO records Vol. 46 Page(s) 17602)

-----  
The ¼ sec. cor., perpetuated and recorded by Byron in 1956, monumented with an iron post 1½" dia., firmly set, projecting 12" above ground, with brass cap mkd. in 1956, from which the remains of the original bearing trees:

A Fir stub 16" dia., bears S.60°E., 25 lks. dist., with scribe marks BT visible on an opened blaze.

A rootcrown bears West, 11 lks. dist., with a down Fir alongside, 20" dia., no marks visible.

and bearing trees mkd. by Byron:

A Fir 10" dia., bears S.51°E., 25½ lks. dist. with scribe marks 31 visible on a partially healed blaze.

A Fir 19" dia., bears N.32°W., 27 lks. dist., with a healed blaze.

and a tree not of known record:

A Fir 15" dia., bears N.38½°W., 25½ lks. dist., with a healed blaze.

and a new bearing tree:

A Fir 12" dia., S.63¼°E., 17 lks. dist., mkd. ¼ S31 BT.

continued next page

TOWNSHIP 23 RANGE 07 POINT IDENTIFIER # 100140

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 31; and 36, T23-8

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

David Edwards - Crew: Brant Miller & Eric Sprinkle - 8/7/2017  
- C.S. File 65/95-57

-----  
Found - 1956 D.C.S. brass capped iron pipe in good  
condition.

The only remaining BTs noted in the 1982 B.L.M.  
visit are as follows:

A 15" dia. Fir snag with healed blaze bears  
S.63¼°E., 11.2 ft.

A 16" dia. Fir snag with healed blaze bears S.51°E.,  
16.8 ft.

New - A 16" dia. Fir scribed ¼ S31 BT bears S.79°E., 19.7 ft

A 15" dia. Fir scribed ¼ S 36 BT bears S.77°W., 12.3 ft

A six foot steel post is set 2 feet South.