

TOWNSHIP 23 RANGE 07 POINT IDENTIFIER # 100200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 30 & 31; 25 & 36, T23-8

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by Thomas H. Hutchinson, Deputy Surveyor, under Contract #60, dated July 19, 1855 - (DCSO records Vol. 6 Page(s) 2460)

Set post cor. to secs. 30, 31, 25 and 36, from which
A Fir 10" dia., bears N.67°W., 98 lks. dist.
A Fir 10" dia., bears S.50°W., 130 lks. dist.
A Fir 40" dia., bears S.85°E., 335 lks. dist.
A Fir 12" dia., bears N.4°E., 158 lks. dist.

Douglas Co. Surveyors Office - James Byron, Deputy - Milo Godfrey; S. Bilow, crew - Dec. 19, 1957 - C.S. File 49/49-1

Found - Orig. 10" now 24" Fir snag, N.67°W., 64.7 ft., open face, good scribing.
Orig. 10" now 24" Fir snag, S.50°W., 85.8 ft. I open and find good scribing.
Find what may be orig. 24" now 30" Fir, N.4°E., 104.3 ft. Shows old scar. I do not open.
Find rotted stump for orig. SE. BT.

Set Brass cap at cor. mkd: County Surveyors Office
T 23 S
R8W S 25 | S 30 R7W
S 36 | S 31
1957

New BTs- 7" R.Fir bears S.45°E., 16.6 ft. scribed T23S R7W S31 CS BT.
8" R.Fir bears S.32°W., 9.2 ft. scribed T23S R7W S30 CS BT.
10" R.Fir bears N.43½°E., 13.6 ft. scribed T23S R7W S30 CS BT.
6" R.Fir bears N.67°W., 11.2 ft. scribed T23S R8W S25 CS BT.

Fd. and used in BLM resurvey by Floyd Brooks and Peter Peterson, Cadastral Surveyors - under Group # 518 - surveyed June/July 1963 - (DCSO records Vol. 32 Page(s) 13529-30)

Fd. OK, March 1983 by D. Bentz - M 90-38 A&B