

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Thomas H. Hutchinson, Deputy Surveyor, under Contract #60, dated July 19, 1855 - (DCSO records Vol. 6 Page(s) 2459-60)

Set post cor. to secs. 19 and 30, 24 and 25, from which
A Fir 60" dia., bears N.25°W., 95 lks. dist.
A Fir 30" dia., bears N.62°E., 438 lks. dist.
A Fir 40" dia., bears S.8°E., 650 lks. dist.
A W.Oak 14" dia., bears S.16°W., 650 lks. dist.

Fd. and used in GLO survey by William R. Whipple, Deputy Surveyor, under Contract #622, dated June 23, 1893 (DCSO records Vol. 6 Page(s) 2612)

BLM resurvey by Floyd Brooks and Peter Peterson, Cadastral Surveyors - under Group # 518 - surveyed June/July 1963 - (DCSO records Vol. 32 Page(s) 13531)

Point for the sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 28" long, 2 1/2" dia., 22" in the ground, with brass cap mkd:
T 23 S
R 8 W R 7 W
S 24 | S 19
S 25 | S 30
1964

from which
A Fir 18" dia., bears N.6°E., 406 lks. dist. mkd. T23S R7W S19 BT.
A Fir 37" dia., bears N.39°W., 571 lks. dist. mkd. T23S R8W S24 BT.

No suitable bearing trees available within limits in secs. 25 and 30.
Set a steel fence post, 6 ft. long, 2 ft. in the ground, alongside the iron post.

From this point, United States Coast and Geodetic Survey triangulation station KELLOG, 1953, bears S.11°48'E., 8.91 chs. dist., monumented with a standard 3" brass cap set in an iron post 3" dia., projecting 4" above ground.

Fd. and used in BLM survey by Harvey E. Wofford, Cadastral Surveyor, under Group #987, surveyed July/Nov. 1979 - (DCSO records Vol. 42 Page(s) 16586)

Brass cap found OK, March 1983 by D. Bentz - M 90-38 A&B

(Cont. Next Page)

TOWNSHIP 23 RANGE 07 POINT IDENTIFIER # 100300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 19 & 30; 24 & 25, T23-8

Alias_____	Description_____
Alias_____	Description_____
Alias_____	Description_____
Alias_____	Description_____

Douglas Co. Surveyors Office - Larry E. Monrean, Deputy -
Randall Smith and Stephen Flause, crew - May 30, 1984 - C.S.
File 62/18-8

Found - BLM 1964 2½" iron pipe with brass cap, properly mkd.
protruding 6" above ground.
18" now a 28" dia. D.Fir with a single healed blaze,
bears N.6°E., 268.0 ft. (1964)
37" now a 42" dia. D.Fir with a single healed blaze,
bears N.39°W.,, 376.9 ft. (1964)
A steel fence post 6 ft. long, set 2 ft. in the
ground, is alongside East edge of iron pipe.
A 12" rebar 5 ft. long, set 2 ft. in the ground, is
alongside West edge of iron pipe.
New BTs- 4" dia. D.Fir double blazed and scribed "X BT",
bears S.46°W., 20.6 ft.
4" dia. D.Fir, double blazed and scribed "X BT",
bears S.86°E., 81.5 ft.
Corner lies on a gentle North slope. (Map number M 90-38 A
shows NE. and NW. BTs as not found.)